

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-045-29664

Indicate Type of Lease

STATE ☐

FEE ☒

State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

Name of Operator
Cross Timbers Operating Company

Address of Operator
6001 Highway 64, Farmington, NM 87401

Well Location

Unit Letter M : 1130 Feet From The South Line and 840 Feet From The West Line

27 Section 30N Township 12W Range NMPM San Juan County

Elevation (Show whether DF, RKB, RT, GR, etc.)
GR 5534'

RECEIVED
OCT 29 1998
OIL CON. DIV.
DIST. 3

Lease Name or Unit Agreement Name
Duff Gas Com C

Well No.

Pool name or Wildcat
Basin Fruitland Coal

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Running 4-1/2" production casing ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 6-1/4" hole to 1,856', T.D., 10/22/98. Circulated hole clean. RU Schlumberger and ran DIL/GR/SP/LDT/CNL/Cal from LTD 1848' to 130'. RD Schlumberger. Ran new 4-1/2", 10.5#, J-55, STC casing and set @ 1,856'. RU Dowell and cemented w/100 sx 35/65 Pozmix CI "B" cement w/6% gel, 5#/sx gilsonite & 1/4#/sx Celloflake followed w/100 sx CI B cement w/5#/sx gilsonite & 1/4#/sx Celloflake. Displaced w/29 bbls fresh water. Plug down @ 6:15 p.m., 10/22/98 w/1074 psig. Float held OK. Circulated 20 sx cement to surface. ND BOP. Set slips. Released rig @ 7:15 p.m., 10/22/98.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bobby L. Smith TITLE Drilling/Operations Manager DATE 10-23-98

TYPE OR PRINT NAME Bobby L. Smith

TELEPHONE NO. 505/632-5200

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. FERREN

APPROVED BY

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 29 1998