

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

| |
|--|
| WELL API NO. 30-045-29665 |
| Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| State Oil & Gas Lease No. |
| Lease Name or Unit Agreement Name McCoy Gas Com D |
| Well No. 2 |
| Pool name or Wildcat Basin Fruitland Coal (71629) |

| | |
|---|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | |
| Name of Operator Crss Timbers Operating Company | Well No. 2 |
| Address of Operator 6001 Highway 64, Farmington, NM 87401 | Pool name or Wildcat Basin Fruitland Coal (71629) |
| Well Location Unit Letter <u>A</u> : <u>920</u> Feet From The <u>North</u> Line and <u>805</u> Feet From The <u>East</u> Line <u>28</u> Section <u>30</u> <u>32N</u> Township <u>12W</u> Range <u>NMPM</u> <u>San Juan</u> County | |
| Elevation (Show whether DF, RKB, RT, GR, etc.) GR 5456' | |

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Running 4-1/2" casing ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1742', TD, 12/03/98. RU & ran new 4-1/2", 10.5#, J-55, STC casing and set @ 1741'. RU Dowell/Schlumberger and cemented w/100 sx 35/65 Poz B cement w/6% gel, 5#/sx gilsonite & 1/4#/sx celloflake followed by 100 sx CI B cement w/5#/sx gilsonite & 1/4#/sx celloflake. Displaced cement w/27 bbls fresh water. Did not bump plug. Circulated 3 sx of good cement to surface. Plug down @ 3:15 a.m. w/800 psig (0 psig over final displacement pressure), 12/04/98. ND BOP, set slips & cut off casing. Released rig @ 5:15 a.m., 12/4/98. WOC.

RECEIVED
DEC 10 1998
OIL CON. DIV
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bobby L. Smith TITLE Drilling/Operations Manager DATE 12-08-98

TYPE OR PRINT NAME Bobby L. Smith TELEPHONE NO. 915/682-8873

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

APPROVED BY _____ TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #3 DATE DEC 10 1998

CONDITIONS OF APPROVAL, IF ANY: