Form 3160-5 (June 1990)

UNITED STATES OF THE INTERIOR

FORM APPROVED

Budget Bur	eau No.	. 10	04-0135	
Expires:	March	31,	1993	

BUREAU OF LAND MANAGEMENT EECELVES	Expires: March 31, 1993
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different eseryor. PH Use "APPLICATION FOR PERMIT -" for such proposals."	2: 23 5. Unase Designation and Serial No. SF-081098-A 6. Il Indian, Allottee or Tribe Name
1. Type of Well Old Well Gas 2. Name of Operator AMOCO PRODUCTION COMPANY Gail M. Jefferson	
73. Address and Telephone No. P.O. BOX 800 DENVER, COLORADO 80201 (303) 830-6	3004529674 3004529674 Blanco Mesaverde
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2060' FSL 1715' FEL Sec. 3 T 30N R 9W L	JNIT J SAN JUAN NEW MEXICO
2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NATURE	OTICE , REPORT, OR OTHER DATA PE OF ACTION
Notice of Intent Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Spud and Set Sundry Other Spud and Set Sundry	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.
13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If markers and zones pertinent to this work.)*	well is directionally drilled, give subsurface locations and measured and true vertical depths for all

MIRU spud a 12.25" surface hole on 11/11/98 at 16:00 hrs. Drilled to 289'. Set 9.625" 36# K-55 surface pipe at 282'. Cemented with 152 sxs Class B cmt. Cemented pipe to surface circulating 70 sxs good cement to surface with no fall back. Pressure tested to 1200#.

Drill an 8.750" intermediate hole on 11/14/98 at 10:30 hrs. Drilled to 3000'. Set 7" 20 & 23# K-55 intermediate casing at 3004'. Cemented with 201 sxs CI B lead and 150 sxs of CI B tail. Stage one circulated poorly and did not circ cmt. Stage two had good circulation and circulated 10 bbls of good cmt to surface. Pressure tested to 1200#.

Drill 6.25" hole to 5356' on 11/17/98. Set. 4.500 10.5# . J-55 production liner at 5364'. Cemented with 300 sxs CI B. Circulated 8 bbls good cmt to surface. Pressure tested to 1200.

Rig released 18:00 hrs on 11/19/98.

A. I hereby certify that the topogoing true and correct Signed Signed	Title _	Sr. Admin. Staff Asst.	weepter for secur
his space for Federal or State office use)	Title —		DEC 16 1998
Approved by Conditions of approval, if any:			ARMINGTON JISTRICT DEV