

(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0735
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals

RECEIVED
BLM

98 NOV 18 PM 12:48

070 FARMINGTON, NM

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
AMOCO PRODUCTION COMPANY
Attention: Gail M. Jefferson

3. Address and Telephone No.
P.O. BOX 800 DENVER, COLORADO 80201 (303) 830-6157

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2430' FNL 1565' FEL Sec. 18 T 30N R 9W UNIT G

5. Lease Designation and Serial No.

SF-080243

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Florance Gas Com I #13B

9. API Well No.

3004529675

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

SAN JUAN NEW MEXICO

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud and Set Report

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU spud a 12.25" surface hole on 11/5/98 at 20:30 hrs. Drilled to 285'. Set 9.625" 36# surface pipe at 282'. Cement with 213 sxs Class B cement. Cemented pipe to surface circulating 75 sxs clabbered mud and 25 sxs of good cement to surface with no fall back.

Drill a 8.750" intermediate hole on 11/7/98 at 15:30 hrs. Drilled to 2,960'. Set 7" 20 and 23# intermediate casing at 2962'. Cemented with 207 sxs Class B lead and 150 sxs of Class B tail. Circulated 13 bbls of good cmt to surface. Pressure test to 1200#.

Drill a 6.250" hole to 5402' on 11/10/98. Set 4.50" 10.5# production liner at 5398'. Cemented with 268 sxs Class B. Circulated 12 sxs of good cement to surface. Top L. 2747

Rig released at 08:00 hrs on 11/11/98.

RECEIVED
BLM

14. I hereby certify that the foregoing is true and correct

Signed

Gail M. Jefferson

Title

Sr. Admin. Staff Asst.

Date

11-16-1998

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

DEC 03 1998

* See Instructions on Reverse Side

AMOCO

FARMINGTON DISTRICT OFFICE
BY [Signature]