

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-045-29738

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
Cross Timbers Operating Company

3. Address of Operator
2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401

7. Lease Name or Unit Agreement Name
Stedje Gas Com

8. Well No.
2

9. Pool name or Wildcat
Basin Fruitland Coal (71629)

4. Well Location
Unit Letter A : 1,175 Feet From The North Line and 675 Feet From The East Line

Section 27 Township 30N Range 12W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
5,474' GR 5,478' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug and abandon the subject well as follows:

Set 4-1/2" cement retainer @ 1,358'. Pump 41 sacks class "B" cement below retainer & spot 12 sacks class "B" cement above retainer in casing (1,252' to 1,629').
Pull up hole to 720' & spot 30 sacks class "B" cement (375' to 720') to cover Kirtland & Ojo Alamo tops.
Pull up hole to 212' & spot 20 sacks class "B" cement (surface to 212'). Circulate good cement out of casing valves. TOH with tubing.
Cut off casing below surface & install dry hole marker.
Restore portion of location not being used by other wells.

It is planned to Plug & abandon this well within the next 5 weeks.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Thomas DeLong TITLE Operations Engineer DATE 5/11/2000

TYPE OR PRINT NAME Thomas DeLong TELEPHONE NO. (505)324-1090

(This space for State Use)

Original Signed by **STEVEN N. HAYDEN**

DEPUTY OIL & GAS INSPECTOR, DIST. III

MAY 11 2000

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: