

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1450' FNL, 790' FWL, Sec.13, T-31-N, R-7-W, NMPM

5. Lease Number  
NM-03358

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
Northeast Blanco Unit

8. Well Name & Number  
Northeast Blanco U#311

9. API Well No.  
30-045-29860

10. Field and Pool  
Blanco MV/Basin DK

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input checked="" type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-200'	Spud	8.4-9.0	No control
200-3637'	LSND	8.4-9.0	No control
3637-8083'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
14 3/4"	0-200'	11 3/4"	42#	H-40
10 5/8"	0-3637'	8 5/8"	32#	J-55
7 7/8"	0-8083'	5 1/2"	15.5#	K-55

Cementing Program:

11 3/4" surface casing - 220 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (260 cu.ft. of slurry, 200% excess to circulate to surface).  
 8 5/8" intermediate casing - lead w/549 sx Class "B" cement with 3% Econolite, 10 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.25 pps Flocele (1719 cu.ft. of slurry, 125% excess to circulate to surface).  
 5 1/2" production liner - cement with 750 sx Class "B" 50/50 poz w/3% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.7% fluid loss, 0.15% retardant (1103 cu.ft., 40% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed Tammy Wimsatt for Title Regulatory Supervisor Date 8/15/00  
TLW

(This space for Federal or State Office use)

APPROVED BY /s/ Jim Lovato Title \_\_\_\_\_ Date AUG 22 2000

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB