UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

| | es and Reports on Wells | J 1.1 4 4 | 4 |
|--|---|---|--|
| Type of Well GAS | | 5. | Lease Number SF-078201 If Indian, All. or Tribe Name |
| . Name of Operator | - TERENTE | 2 J 7. | Unit Agreement Nam |
| BURLINGTON RESOURCES OIL & | GAS COMPANY | OMO- | |
| . Address & Phone No. of Operator | |) (3) | Well Name & Number Riddle A #3B |
| PO Box 4289, Farmington, NM 8 | | 9. | 30-045-27873 |
| Location of Well, Footage, Sec. 1010'FNL 915'FWL, Sec.24, T-30- | | | Field and Pool Blanco Mesaverde County and State San Juan Co, NM |
| 2. CHECK APPROPRIATE BOX TO INDIC | | RT, OTHER | DATA |
| Type of Submission Notice of Intent | Type of Action Abandonment Char | nge of Pla | ans |
| | | Construc | |
| - - | | | Fracturing |
| _ | | er Shut o | |
| Final Abandonment | Altering Casing Conv X Other - Casing & cement | ersion to | o Injection |
| <u>-</u> | coner caping a comenc | | |
| 3. Describe Proposed or Complet | ted Operations | | |
| | | | ₹ |
| 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w, s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to | 23# J-55 a /3% econol iled w/90 0.5 pps fi surface. | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. |
| 8-11-99 TIH w/5 jts 7" 23# 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 PT BOP & csg to | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w/ s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to 5 1500 psi/30 mins, OK. Dril | 23# J-55 a /3% econol iled w/90 0.5 pps fi surface. | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. |
| 8-11-99 TIH w/5 jts 7" 23# 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 PT BOP & csg to 8-12-99 Drill to TD @ 5170 8-13-99 TIH w/58 jts 4 ½" Cmtd w/300 sx 0 | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w/s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to 0 1500 psi/30 mins, OK. Dril 0'. Circ hole clean. TOOH. 10.5# J-55 ST&C csg, set @ Class "H" 50/50 poz w/2% gel & Halad-344, 0.1% HR-5, 0.2% | 23# J-55 : /3% econol iled w/90 0.5 pps fi surface. lling ahe 5155'. Li 1, 0.25 p | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. ad. pr top @ 2663'. ps flocele, 5 pps |
| 8-11-99 TIH w/5 jts 7" 23# 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 PT BOP & csg to 8-12-99 Drill to TD @ 5170 8-13-99 TIH w/58 jts 4 ½" Cmtd w/300 sx 0 gilsonite, 0.4% | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w/s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to 0 1500 psi/30 mins, OK. Dril 0'. Circ hole clean. TOOH. 10.5# J-55 ST&C csg, set @ Class "H" 50/50 poz w/2% gel & Halad-344, 0.1% HR-5, 0.2% | 23# J-55 : /3% econol iled w/90 0.5 pps fi surface. lling ahe 5155'. Li 1, 0.25 p | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. ad. pr top @ 2663'. ps flocele, 5 pps |
| 8-11-99 TIH w/5 jts 7" 23# 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 PT BOP & csg to 8-12-99 Drill to TD @ 5170 8-13-99 TIH w/58 jts 4 ½" Cmtd w/300 sx 0 gilsonite, 0.4% NU WH. RD. Rig | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w/s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to 0 1500 psi/30 mins, OK. Dril 0'. Circ hole clean. TOOH. 10.5# J-55 ST&C csg, set @ Class "H" 50/50 poz w/2% gel & Halad-344, 0.1% HR-5, 0.2% released. | 23# J-55 : /3% econo. iled w/90 0.5 pps f: surface. lling ahe: 5155'. Li 1, 0.25 pp | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. ad. pr top @ 2663'. ps flocele, 5 pps |
| 8-11-99 TIH w/5 jts 7" 23# 2799'. Cmtd w/3 flocele, 10 pps 50/50 poz w/2% gilsonite (127 PT BOP & csg to 8-12-99 Drill to TD @ 5170 8-13-99 TIH w/58 jts 4 ½" Cmtd w/300 sx 0 gilsonite, 0.4% NU WH. RD. Rig | N-80 LT&C csg & 62 jts 7" 2 312 sx Class "B" neat cmt w/s gilsonite (852 cu ft). Tai gel, 2% calcium chloride, (cu ft). Circ 20 bbl cmt to 0 1500 psi/30 mins, OK. Dril 0'. Circ hole clean. TOOH. 10.5# J-55 ST&C csg, set @ Class "H" 50/50 poz w/2% gel & Halad-344, 0.1% HR-5, 0.2% released. | 23# J-55 s /3% econo iled w/90 0.5 pps f surface. lling ahea 5155'. La 1, 0.25 pps 6 CFR-3 (S | ST&C csg, set @ lite, 0.5 pps sx Class "B" locele, 10 pps WOC. NU BOP. ad. ar top @ 2663'. as flocele, 5 pps 396 cu ft). ND BOP. |

FARMINGTON FIELD OFFICE