UNITED STATES

DEPARTMENT OF THE INTERIOR BURBAU OF LAND MANAGEMENT

r = 3:52

	Sundry Not	ices and Reports on Wells	
		and the second s	
		Section 2	5. Lease Number SF-078138
. Type of We	- 11	A service of the serv	6. If Indian, All. or
GAS	377		Tribe Name
22.2.0		SPARIO	
			Unit Agreement Na
. Name of Op	perator	act c	(A)
BURI	INGTON	60 OCT - 8 °	1943
ALSO	ORCES OIL	& GAS COMPANY	8. Well Name & Numbe
Address &	Phone No. of Opera		Manual R Com #103
PO Box 4	289, Farmington, NM	1 87499 (505) 326-9700	9. API Well No.
			• • • • • • • • • • • • • • • • • • • •
. Location	of Well, Footage, S	Sec., T, R, M	10. Field and Pool Blanco Mesaverde
800'FSL,	1525'FWL, Sec.22, T	C-30-N, R-11-W, NMPM	11. County and State
	N		San Juan Co, NM
	! 	NDICATE NATURE OF NOTICE, REPOR	
_ _	ubsequent Report	Plugging Back Non-	
F 3. Descri 9-10-9 9-11-9	be Proposed or Comp Prill to TD @ 51 TIH w/113 jts 4 Cmtd w/720 sx Cl gilsonite, 0.1 poz w/0.25 pps (557 cu ft).	Plugging Back Non- Casing Repair Wate Altering Casing Conv X_ Other - casing, & cemer Pleted Operations 110'. Circ hole clean. TOOH. %" 10.5# J-55 ST&C csg, set @ lass "H" 50/50 poz w/2% gel, 0 1% HR-5 (900 cu ft). Tailed w/4 s flocele, 7 pps gilsonite, 0.4 Circ 30 bbl cmt to surface. Cap	Routine Fracturing er Shut off version to Injection of the state of th
9-10-9 9-11-9 9-12-9	be Proposed or Comp 9 Drill to TD @ 51 9 TIH w/113 jts 4 9 Cmtd w/720 sx Cl gilsonite, 0.1 poz w/0.25 pps (557 cu ft). (neat cmt w/3% RD. Rig releas	Plugging Back Non- Casing Repair Water Altering Casing Conv. X Other - casing, & cemer Collected Operations 110'. Circ hole clean. TOOH. %" 10.5# J-55 ST&C csg, set @ lass "H" 50/50 poz w/2% gel, 0.1% HR-5 (900 cu ft). Tailed w/4 s flocele, 7 pps gilsonite, 0.4 circ 30 bbl cmt to surface. Cap calcium chloride (120 cu ft).	Routine Fracturing or Shut off version to Injection of the state of th
9-10-9 9-11-9 9-12-9	be Proposed or Comp 9 Drill to TD @ 51 9 TIH w/113 jts 4 9 Cmtd w/720 sx Cl gilsonite, 0.3 poz w/0.25 pps (557 cu ft). 0 neat cmt w/3% RD. Rig release	Plugging Back Non Nate and Casing Repair Wate altering Casing Convolutions X_ Other - casing, & cemer color of the clean in the color of the clean in the color of the clean in the cle	Routine Fracturing or Shut off version to Injection of the state of th
9-10-9 9-11-9 9-12-9	be Proposed or Comp 9 Drill to TD @ 51 9 TIH w/113 jts 4 9 Cmtd w/720 sx Cl gilsonite, 0.1 poz w/0.25 pps (557 cu ft). (neat cmt w/3% RD. Rig releas	Plugging Back Non Nate and Casing Repair Wate altering Casing Convolutions X_ Other - casing, & cemer color of the clean in the color of the clean in the color of the clean in the cle	Routine Fracturing or Shut off version to Injection of the state of th