Form 3160-5 FORM APPROVED (June 1990) Budget Bureau No. 1004-0135 Expires: March 31, 1993 99 MAY 13 AM 11:21 5. Lease Designation and Serial No. **UNITED STATES** DEPARTMENT OF THE INTERIOR SF - 378214 BUREAU OF LAND MANAGEMENT FARMINGTON, NM 6. If Indian, Allottee or Tribe Name SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir, 7. If Unit or CA. Agreement Designation Use "APPLICATION FOR PERMIT--" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. TIGER #11 Oil Well X Gas Well Other 2. Name of Operator 9. API Well No. 30-045-29927 ROBERT L. BAYLESS, PRODUCER LLC 10. Field and Pool, or Exploratory Area 3. Address and Telephone No. **BASIN FRUITLAND COAL** P.O. BOX 168, FARMINGTON, NM 87499 (505) 326-2659 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 1755' FSL & 1030' FWL, SEC. 27, T30N, R13W SAN JUAN, NEW MEXICO CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Abandonment Change of Plans New Construction Notice of Intent Recompletion Non-Routine Fracturing Plugging Back Casing Repair Water Shut-Off X Subsequent Report Altering Casing Conversion to Injection Other SPUD, CEMENT Dispose Water Final Abandonment Notice CASING (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is

directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PLEASE SEE ATTACHED MORNING REPORT.

Title Engineer	Date May 12, 19	
Title	Date	
·		
		TED DE
n knowingly and willfully to make	to any department or agency of the U	nited States any false,
		n knowingly and willfully to make to any department or agency of the U

TO ICLE UTTIVE

## ROBERT L. BAYLESS, PRODUCER LLC

Tiger #11 1755 FSL & 1030 FWL SECTION 27, T30N, R13W

## MORNING REPORT-DRILLING

5/11/99

Build location and line drilling pit. Move L&B rig onto location. Shut down overnight.

5/12/99

Rig up drilling rig and spud well at 8:30 am, 5/11/99. Drill 8 ¾" hole to 124 feet. Circulate hole clean and drop deviation tool. Trip out of hole. Deviation ¼° at 124 feet. Run 4 joints (121.30 feet) 7 " 23.0 #/ft J-55 casing, landed at 123 feet. Rig up Cementers Inc and cement casing with 65 sx (77 cf) Class B with 4% CaCl and ¼ #/sack cello-flake. Good returns throughout job with 4 bbls of good cement circulated to pit. Plug down at 1:45 pm, 5/11/99. WOC for 4 hours and break off cementing head. Nipple up BOP and choke manifold. Pressure test BOP to 500 psi for 30 minutes, held OK. Pressure test choke manifold to 500 psi for 30 minutes, held OK. Shut down overnight.