UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

•	otices and Reports on Wells.	* * * * * * * * * * * * * * * * * * *	
		5,.	Lease Number SF-078505
Type of Well GAS		6.	If Indian, All. or Tribe Name
		7.	Unit Agreement Name
Name of Operator BURLINGTON RESOURCES OI	IL & GAS COMPANY		
. Address & Phone No. of Ope		8. 9.	Seymour #3C
PO Box 4289, Farmington,	NM 67499 (543), 348-2700	; 9.	30-045-29959
1. Location of Well, Footage,		10.	Field and Pool
2100'FNL, 660'FEL, Sec.24,	T-31-N, R-9-W, NMPM	11.	Blanco Mesaverde County and State San Juan Co, NM
2. CHECK APPROPRIATE BOX TO	INDICATE NATURE OF NOTICE, REPORT	r, other	DATA
Type of Submission Notice of Intent	Type of Action Abandonment Change Recompletion New C	Construc	tion
X Subsequent Report	Plugging Back Non-F Casing Repair Water		Fracturing ff
Final Abandonment	Altering Casing Conve		
	X Other - casing, & cement		
7-8-00 Drill to inter 23# N-80 LT& tool set @ 2 calcium chlo Circ 5 bbl c sodium metal 31 bbl cmt t 7-9-00 PT BOP & csg t 7-11-00 Drill to TD @ ST&C csg, se poz w/3% gel (363 cu ft).		csg, se ss "B" ! .25 pps 62 sx C s gilsor ahead. H w/60 ; w/250 s	et @ 3120'. Stage 50/50 poz w/2% flocele (290 cu ft). lass "B" cmt w/3% mite (762 cu ft). Cir its 4 %" 10.5# J-55 ex Class "B" 50/50 HR-5, 0.2% CFR-3
7-8-00 Drill to inter 23# N-80 LT& tool set @ 2 calcium chlo Circ 5 bbl c sodium metal 31 bbl cmt t 7-9-00 PT BOP & csg t 7-11-00 Drill to TD @ ST&C csg, se poz w/3% gel (363 cu ft). released.	ompleted Operations mediate TD @ 3135'. Circ hole clo aC csg, & 69 jts 7" 20# J-55 ST&C 2237'. Cmtd 1st stage w/218 sx Cla oride, 2% gel, 5 pps gilsonite, 0 cmt to surface. Cmtd 2nd stage w/2 silicate, 0.25 pps flocele, 5 pp co surface. WOC. co 1500 psi/30 min, OK. Drilling 5554'. Circ hole clean. TOOH. TI et @ 5526'. Lnr top @ 2982'. Cmtd 1, 5 pps gilsonite, 0.5% Halad-34 . Circ 13 bbl cmt to surface. ND	csg, sess "B" 5 .25 pps 62 sx Cls gilson ahead. H w/60 5 w/250 s 4, 0.1% BOP. NU	et @ 3120'. Stage 50/50 poz w/2% flocele (290 cu ft). lass "B" cmt w/3% mite (762 cu ft). Cir its 4 %" 10.5# J-55 ex Class "B" 50/50 HR-5, 0.2% CFR-3
7-8-00 Drill to inter 23# N-80 LT& tool set @ 2 calcium chlo Circ 5 bbl c sodium metal 31 bbl cmt t 7-9-00 PT BOP & csg t 7-11-00 Drill to TD @ ST&C csg, se poz w/3% gel (363 cu ft). released.	ompleted Operations mediate TD @ 3135'. Circ hole cla ac csg, & 69 jts 7" 20# J-55 ST&C 2237'. Cmtd 1st stage w/218 sx Cla bride, 2% gel, 5 pps gilsonite, 0 cmt to surface. Cmtd 2nd stage w/2 asilicate, 0.25 pps flocele, 5 pp co surface. WOC. co 1500 psi/30 min, OK. Drilling 5554'. Circ hole clean. TOOH. TI et @ 5526'. Lnr top @ 2982'. Cmtd 1, 5 pps gilsonite, 0.5% Halad-34	csg, sess "B" ! .25 pps 62 sx Cl s gilsor ahead. H w/60 : w/250 s 4, 0.1% BOP. NU	et @ 3120'. Stage 60/50 poz w/2% flocele (290 cu ft). Lass "B" cmt w/3% wite (762 cu ft). Cir ts 4 %" 10.5# J-55 ex Class "B" 50/50 HR-5, 0.2% CFR-3 WH. RD. Rig
7-8-00 Drill to inter 23# N-80 LT& tool set @ 2 calcium chlo Circ 5 bbl c sodium metal 31 bbl cmt t 7-9-00 PT BOP & csg t 7-11-00 Drill to TD @ ST&C csg, se poz w/3% gel (363 cu ft). released.	ompleted Operations mediate TD @ 3135'. Circ hole cla cc csg, & 69 jts 7" 20# J-55 ST&C 2237'. Cmtd 1st stage w/218 sx Cla oride, 2% gel, 5 pps gilsonite, 0 cmt to surface. Cmtd 2nd stage w/2 silicate, 0.25 pps flocele, 5 pp to surface. WOC. to 1500 psi/30 min, OK. Drilling 5554'. Circ hole clean. TOOH. TI cet @ 5526'. Lnr top @ 2982'. Cmtd d., 5 pps gilsonite, 0.5% Halad-34 d. Circ 13 bbl cmt to surface. ND the foregoing is true and correct Title Requlatory Super	csg, sess "B" ! .25 pps 62 sx Cl s gilsor ahead. H w/60 : w/250 s 4, 0.1% BOP. NU	et @ 3120'. Stage 50/50 poz w/2% flocele (290 cu ft). Lass "B" cmt w/3% lite (762 cu ft). Cir lits 4 %" 10.5# J-55 ex Class "B" 50/50 HR-5, 0.2% CFR-3 WH. RD. Rig