

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Richardson Operating Company

3. Address and Telephone No.

1700 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000

4. Location of Well (Footage, T, R, M, or Survey Description)

1086' FNL & 866' FEL

Sec. 20-T30N-R14W

5. Lease Designation and Serial No.

NM-25857

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

WF Federal 20-2

9. API Well No.

30-045-30062

10. Field and Pool, or Exploratory Area

Fruitland Coal/Twin Mounds PC Ext.

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Surface Casing/Cementing
☒ Other: see below

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form).

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.

If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)*

6-5-00 Spud 8 3/4" surface hole. Drill to 135'. Ran 3 jts 7" 20# casing and set at 132.92'. Cemented with 30 sxs Class "B" cement with CaCl2. Circulated 4 bbls cement to surface.

6-6-00 Test BOP and 7" casing to 2000# for 30 minutes. Began drilling to TD.

6-8-00 Drill to 1325' TD. Run 30 jts 4 1/2" 10.5# casing to 1322.67'. Cemented with 75 sxs (155 cuft) of Class "B" cement with 2% metasilicate and 75 sxs (89 cuft) of Class B Neat. Circulated 4 bbls cement to surface. Plug down at 10:40 am.

14. I hereby certify that the foregoing is true and correct

Signed: *Cathleen Kelly*

Title: Land Manager

(This space for Federal or State office use)

Approved by:

Title:

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD
Date: June 16, 2000

Date: JAN 29 2001

FARMINGTON FIELD OFFICE

BY *[Signature]*