


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir,
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE



FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Lease Designation and Serial No.
NM-04444

If Indian, Allottee or Tribe Name

If Unit or CA. Agreement Designation

Northeast Hogback Unit

8. Well Name and No.
NEHB #53

9. API Well No.
30-045-30091

10. Field and Pool, or Exploratory Area
Horseshoe Gallup

11. County or Parish, State
San Juan County, NM

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other WIW

2. Name of Operator
Central Resources, Inc. c/o Playa Minerals & Energy, Inc.

3. Address and Telephone No.
650 N. Sam Houston Pkwy. E. Suite 500 Houston, Tx 77060 (281) 931-3800

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1350' FSL, 1120' FEL, Sec. 10, T30N, R16W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud/ Casing Notice

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

L&B Speed Drill spudded well on 1/25/00. Drilling 8-3/4" hole.

1/26/00 Set 7", 23#, J55 casing to 308' with 91 sacks of class B neat cement w/ 2% CaCl and 1/4# cellophane flakes/ sack. Circulated cement to surface.

1/29/00 Drilled 6-1/4" hole 1890'. Set 4-1/2" 9.5#, J-55 casing at 1884' with 95 sacks of lead class B cement containing 3% metasilicate and 1/4# cellophane flakes/ sack and 100 Sacks of tail class B cement containing 3% CaCL and 1/4# cellophane flakes/ sack. Circulated cement to surface. Float collar at 1840'. Centralizers on 1st, 3rd, 5th, 7th, 9th and 11th joints. Pressure tested to 1000#.

14. I hereby certify that the foregoing is true and correct

Signed Mark L. Ehrman Title Regulatory Compliance

Date

ACCEPTED FOR RECORD

(This space for Federal or State office use)

Approved by _____ Title _____ Date

FEB 08 2000

Conditions of approval, if any:

FARMINGTON FIELD OFFICE
BY _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side