

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

810' FNL, 1720' FEL, Sec. 23, T-31-N, R-9-W, NMPM

5. Lease Number

SF-078505

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Seymour #7B

9. API Well No.

30-045-30116

10. Field and Pool

Blanco MV/Basin DK

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☐ Abandonment

☒ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☒ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing and cement program of the subject well.

Mud Program:

Interval	Type	Weight	Vis.	Fluid Loss
0- 200'	Spud	8.4-9.0	40-50	no control
200- 3507'	LSND	8.4-9.0	30-60	no control
3507- 7870'	Gas	n/a	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Csq. Size	Wt.	Grade
12 1/4"	0' - 200'	9 5/8"	32.3#	WC-50
8 3/4"	0' - 3507'	7"	20.0#	J-55
6 1/4"	0' - 7870'	4 1/2"	10.5#	J-55

Tubing Program:

0' - 7870'	2 3/8"	4.70#	EUE	

Cementing:

9 5/8" surface casing - cement with 159 sx Class "B" cement with 1/4# flocele/sx and 3% calcium chloride (188 cu.ft. of slurry, 200% excess to circulate to surface).

7" intermediate casing - Lead w/321 sx Class "B" w/3% sodium metasilicate, 10# gilsonite/sx and 1/2# flocele/sx.

Tail w/90 sx 50/50 Class "B" Poz w/2% calcium chloride, 2% gel (1055 cu.ft. of slurry, 100% excess to circulate to surface.)

7" intermediate casing alternative two stage - Stage collar at 2593'. 1st stage: cement with w/207 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.5 pps Cellophane. 2nd stage: 268 sx Class "B" with 3% sodium metasilicate, 1/2 pps Cellophane, 10 pps Gilsonite (1055 cu.ft., 100% excess to circulate to surface).

4 1/2" Production Liner - Lead with 436 sx 50/50 Class "H" Poz with 2% gel, 0.25# flocele/sx, 5# gilsonite/sx, 0.2% retardant and 0.4% fluid loss additive (641 cu.ft.), 40% excess to cement 4 1/2" x 7" overlap).

Wellhead:

9 5/8" x 7" x 2 3/8" x 3000 psi tree assembly.

14. I hereby certify that the foregoing is true and correct.

Signed Tammy Wimsatt Title Regulatory Supervisor Date 10/4/00
TLW

(This space for Federal or State Office use)

APPROVED BY Jim Lovato Title _____ Date 10/16/00

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

WFOO