

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1655'FNL, 1095'FWL, Sec.30, T-31-N, R-8-W, NMPM

5. Lease Number
SF-078505

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Quinn #2C

9. API Well No.
30-045-30123

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other - casing, & cement	

13. Describe Proposed or Completed Operations

7-14-00 Drill to intermediate TD @ 3443'. Circ hole clean. TOOH. TIH w/5 jts 7" 23# N-80 ST&C csg, & 78 jts 7" 20# J-55 ST&C csg, set @ 3434'. Stage tool set @ 2556'. PT lines to 3000 psi, OK. Cmdt 1st stage w/ 248 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps flocele, 5 pps gilsonite, 0.1% antifoam (312 cu ft). Circ 15 bbl cmt to surface. WOC

7-15-00 Cmdt 2nd stage w/155 sx Class "B" neat cmt w/3% sodium metasilicate, 0.5 pps flocele, 10 pps gilsonite, 0.1% antifoam (450 cu ft). Circ 60 bbl cmt to surface. PT csg & BOP to 1500 psi/30 mins, OK. Drilling ahead.

7-17-00 Drill to TD @ 5848'. Blow well clean. TOOH. TIH w/58 jts 4 1/2" 10.5# J-55 csg, set @ 5833'. Lnr top @ 3322'. PT lines to 3500 psi, OK. Cmdt w/ 256 sx Class "B" 50/50 poz w/4% gel, 0.25 pps flocele, 5 pps gilsonite, 0.35% dispersant, 0.3% fluid loss, 0.2% defoamer (361 cu ft). Circ 10 bbl cmt to surface. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed

Reggie Cole

Title Regulatory Supervisor

ACCEPTED FOR RECORD

TLW

(This space for Federal or State Office use)

APPROVED BY

Title

Date

DEC 12 2000

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.