UNITED STATES DEPARTMENT OF THE INTERIOR



FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 **CUREAU OF LAND MANAGEMENT** 5. LEASE DESIGNATION AND SERIAL NO. SF 078204A SUNDRY NOTICES AND REPORTS ON WELLS IF INDIAN, ALLOTTEE OR TRIBE NAME Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. IF UNIT OR CA, AGREEMENT DESIGNATION SUBMIT IN TRIPLICATE TRIEB FEDERAL TYPE OF WELL 8. WELL NAME AND NO. OIL WELL GAS WELL OTHER #2B 2. NAME OF OPERATOR API WELL NO. CONOCO INC 30-045-30140 ADDRESS AND TELEPHONE NO. 10. FIELD AND POOL, OR EXPLORATORY AREA P.O. Box 2197, DU 3066, Houston, TX 77252-2197 **BASIN DAKOTA** LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 11. COUNTY OR PARISH, STATE 1875' FNL & 660 FEL, SECTION 33, T30N, R10W, UNIT LETTER H SAN JUAN COUNTY CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTIGE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Final Abandonment Notice Casing Repair Water Shut-Off Altering Casing Conversion to Injection Other: Casing Report Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Spudded well at 10:30 p.m. on 6/20/00 Drilled surface hole. Ran 6 joints , 9-5/8" casing set at 292', 36#, J-55, ST&C. Cement with 150 sxs of Type III Neat Cement + 2% CaC12 + .25 LB/SK Cello-Flake at 14.5 ppg. Displaced with 20 bbls fresh water. Circulate to surface. Floats not held. Bumped plug at 1:00 p.m. on 6/21/00 with 500 psi. Ran 51 joints, 7" casing set at 2099', 20#, J-55, ST&C. Lead: Cement with 295 sxs of Premium Lite + 2% CaC12 + 8% Gel + 6/24/00 .25 LB/SK Cello-Flake at 12.1 ppg. Displaced with 81 bbls fresh water. Float held. Bumped plug at 2:30 p.m. on 6/24/00 with 1050 psi. Tail: Cement with 70 sxs of Type III + 2% CaC12 + .25 LB/SK Cello-Flake at 14.5 ppg. 7/11/00 Ran 167 joints, 4-1/2" casing set at 7125', 10.5#, J-55, ST&C. Stage1: Cement with 90 sxs of 35:65 Poz L, Type III H B + .6 BWOC FL-52 + 6.0 BWOC Bentonite + 1.0 BWOC CaC12 Calcium Chlor + .25 LB/SK Cello-Flake + 10.0 LB/SK CSE + .20 BWOC CD-32. Displaced with 112 bbls fresh water/mud. Float Held. Bumped plug at 8:30 a.m. on 7/11/00 with 250 psi. Stage 2: Cement with 145 sxs of 35:65 Poz L Type III Blend + 10.0 LB/SK CSE + .20 BWOC CD-32 + 6.0 BWOC Bentonite + 1.0 BWOC CaC12 Calcium Chlor + .25 BWOC Cello-Flake + .60 BWOC FL-52. Displaced with 96 bbls fresh water/mud. Float held. Bumped plug at 1:00 p.m. on 7/11/00 with 1500 psi. Stage 3: Cement with 100 sxs of 35:65 Poz L Type III + 14.0 BWOC Bentonite + .25 LB/SK Cello-Flake + 1.0 BWOC SM Sodium Metasillcate. Displaced with 66 bbls fresh water. Float not held. Bumped plug at 5:00 p.m. on 7/11/00 with 1500 psi. 14. I hereby certify that the foregoing is true and correct TITLE DEBRA SITTNER, As Agent for Conoco Inc. (This space for Federal or State office use) AUG 2 5 2000 APPROVED BY TITLE DATE Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unites States any lalse,

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.