

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS 2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 1400' FNL, 2295' FEL, Sec. 26, T-30-N, R-11-W, NMPM, San Juan County	API # (assigned by OCD) 30-045-30209 5. Lease Number Fee 6. State Oil & Gas Lease # 7. Lease Name/Unit Name Hartman Com 8. Well No. #4B 9. Pool Name or Wildcat Blanco Mesaverde 10. Elevation:
--	--

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - casing, & cement
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12-14-00 Drill to intermediate TD @ 2695'. Circ hole clean. TOOH. TIH w/ 5 jts 7" 23# N-80 LT&C csg, & 59 jts 7" 20# J-55 ST&C csg, set @ 2685'. Cmted w/306 sx Class "G" 50/50 poz w/2.5% sodium metasilicate, 2% calcium chloride, 10 pps gilsonite, 0.5 pps celloflake, 0.2% antifoam (789 cu ft). Tail w/90 sx Class "G" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps celloflake, 5 pps gilsonite, 0.1% antifoam (115 cu ft). Circ 35 bbl cmt to surface. WOC.

12-15-00 NU BOP. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

12-16-00 Drill to TD @ 5150'. Blow well clean. TOOH. TIH w/119 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 5107'.

12-17-00 Cmted w/275 sx Class "G" 50/50 poz w/4.25% gel, 0.25 pps celloflake, 5 pps gilsonite, 0.25% fluid loss, 0.35% dispersant, 0.1% antifoam, (393 cu ft). ND BOP. NU WH. RD. Rig released.

SIGNATURE *Juan Calle* Regulatory Supervisor January 8, 2001

TLW

(This space for State Use)

Approved by

Title

Date

DEPUTY OIL & GAS SUPERVISOR

JAN - 2001