Form 3160-5		UNITED STATE	es	1	FORM APPROVED	
(June, 1990)	DEPARTMENT OF THE INTERIOR				Budget Bureau No. 1004-0135	
(50.10, 1770)	BUREAU OF LAND MANAGEMENT					
	a. n. 51 ~	MERO OF ERIED MAIN	AGEMEN	-	Expires: March 31, 1993 Lease Designation and Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS					M-25857	
Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.					If Indian, Allotte or Tribe Name	
Use "APPLICATION FOR PERMIT—" for such proposals					II Incian, Audite or The realite	
			such proposals			
4. 7		N TRIPLICATE			If Unit or CA, Agreement Designation	
1. Type of Well	7	1 .		-		
	Oil Well X	Gas Well	Other		Well Name and No.	
2. Name of Op			6 3 3	. —	/F Federal 21-3	
Richardson Operating Company					API Well No.	
3. Address and Telephone No.					0-045-30261	
1700 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000					. Fleid and Pool, or Exploratory Area	
4. Location of Well (Footage, T, R, M, or Survey Description)					arper HII Fruitland Sand PC	
1100' FSL & 1800' FEL					. County or Perieh, State	
Sec. 21-T3		·			an Juan County, NM	
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF S	UBMISSION	ļ	TYPE OF ACTION			
_	7		Abendonment		Change of Plans	
	Notice of Intent		Recompletion	Ш	New Construction	
	¬		Plugging Back	\square	Non-Routine Fracturing	
x	Subsequent Report		Casing Repair		Water Shut-Off	
	- ,		Altering Casing		Conversion to Injection	
	Final Abandonment Notice		Surface Casing/Cementing		Dispose Water	
		<u> </u>	Other: see below	(Note: Rep	ort results of multiple completion on Well	
				Completio	n or Recompletion Report and Log form).	
			and give pertinent dates, including estimated date of s ertical depths for all markets and zones pertinent to thi		proposed work.	
5-17-00 Spud 8 3/4" surface hole. Drill to 137'. Ran 3 jts 7" 20# casing and set at 130'. Cemented with 30 sxs Class "B" cement						
with 2% CaCl2. Circulated 4 bbls cement to surface.						
6-18-00 Test BOP and 7" casing to 2000#. Began drilling to TD.						
6-19-00 Drill to 1465' TD. Run 33 jts 4 1/2" 10.5# casing to 1464'. Cemented with 80 sxs of Class "B" cement with 2%						
	CaCl2 C Lite w/ 1/4# celloflake, and 50 sxs of Class B Neat. Circulated 6 bbls cement to surface. Plug down at 12:52 pm.					
		<u></u> -		 		
			•			
14. I hereby certify that the foregoing is true and correct						
	that the foregoing is true and correct	elle	Title: Land Manager	Ρ.	ACCEPTED FOR RECORD	
Signed:			Title: Land Manager	- Di	ate: July 6, 2000	
(This space for Faderal or State office use)					JAN 2 9 2001	
Approved by: Title: Dat						
Conditions of approval, if any:						
Title 18 U.S.C. S	Section 1001, makes it a crime for	any person knowingly and willfe	ally to make to any department or agency of the United	d States ar	y false, fictitious or fraudulent	