## State of New Mexico

NOV 3 0 2000

\_ DATE \_

OIL CONSERVATION DIVISIO P.O. Boa 1950, Hobbs NM 88211-1980 2040 Pacheco St. Santa Fe, NM 8750 SITERCE STATE P.O. Daver DD, Artesia, NM 88210 State Da	Submit 3 Copies to Appropriate	Energy, Minerals and Nat	ural Resources Depa	artment		n C-103 ised 1-1-89
MOV 2006   Santa Fe, NM 8750   Santa Fe, NM	District Office	OIL CONSERVATI	ON DIVISION	T		
DISTRICT III  POO Traver DD, Artesia, NM 82710  DISTRICT III  1000 Rio Brazos Rd, Azhoc, NM 87410  SUNDRY NOTICES AND REPORTS ON FILL  OTHER  1. Type of Well  WILL WILL OF THE RESERVOIR USE APPLICATION FOR FOR FOR FOR FOR SUNDRY REPORTS ON FILE  2. Name of Operator  Cross Timbers Operating Company  3. Address of Operator  Cross Timbers Operating Company  4. Well Location  Unit Letter M  1. 050 Feel From The South Line and 870 Feel From The West Line  Township 30N Rame  10. Elevation Show whether DP, RKB, RT, CR, etc.)  Section  16. Township 30N Rame  10. Elevation Show whether DP, RKB, RT, CR, etc.)  Section 16. Township 30N Rame  10. Elevation Show whether DP, RKB, RT, CR, etc.)  Section 17. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PULS AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND ABANDON ALTER CASING CHARGE PLANS  OTHER:  12. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propowork) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958 KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers see 165 jts of 4.1/2" casing at 6,953 KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information abovy is trye and complete to the best of my knowledge and belief.  SCANATURE  TILL DRIVING ENTRY DATE  TI		2040 Pache	eco St.	WELL API NO.	45 30272	
SUNDRY NOTICE S AND REPORTS ON SELLO ON		Santa Fe, Ni	M 87505 29 30 311		of Lease	FFF X
SUNDRY NOTICES AND REPORTS ON SELLONG (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DETERN ON THE PROPOSALS THE PROPOS		) )	NOV 2000	State Oil & Gas		FEC LAS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DETECT NOT COMMENCE DRILLING OF NAME OF UNIT Agreement Name Different RESERVOIR USE "APPLICATION FOR SHAPE DIST."  1. Type of Well Will.  OTHER  2. Name of Operator (FORM C-101) FOR SUCH PROPOSALS.)  2. Name of Operator Stripper's Operating Company  3. Address of Operator Proposed or Completed Operations (Show whether DF, RKB, RT, GR, etc.)  3. Address of Operator Proposed or Completed Operations (Show whether DF, RKB, RT, GR, etc.)  5. The Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING THERE TO THERE COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. THERE TAND CEMENT JOB COMMENCE DRILLING OPNS. THERE TAND CEMENT JOB COMMENCE DRILLING OPNS. THERE TAND CEMENT JOB COMMENCE DRILLING OPNS. THERE TO THERE COMMENCE DRILLING OPNS. THERE TO THERE COMMENCE DRILLING OPNS. THE DRIVE OF NOTICE OF THE TOTAL OPERATION OF THE COMMENCE DRILLING OPNS. THE DRIVE OF NOTICE OF THE TOTAL OPERATION OF THE TOTAL OPERATION OF THE TOTAL OPERATION OF THE TOTAL OPPORTUNITY OF THE TOTAL O	SUNDRY NO	TICES AND REPORTS ON				
Type of Well:   WELL   WELL   OTHER	(DO NOT USE THIS FORM FOR F DIFFERENT RES	PROPOSALS TO DRILL OR TO DEEP SERVOIR. USE "APPLICATION FOR	EN OF CHLUCOSACE TO A	Lease Name or	Unit Agreemer	nt Name
2. Name of Operator Cross Timbers Operating Company 3. Address of Operator 2700 Farmington Ave. Bldg. K. Ste 1 Farmington, NM 87401 4. Well Location Unit Letter M. 1.050 Feet From The South Line and 870 Feet From The West Line Section 16 Township 30N Range 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5567 Ground Level 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILLY ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB OTHER: 12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportions of the well. On 11/25/00 Cross Timbers Set 165 jts of 4-1/2" casing at 6.953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  11. Indicate Many All Sections of the well of the best of my knowledge and belief.  12. Schature Date of the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.	1. Type of Well: OIL GAS TY	7	9/101 N 11/19			
Cross Timbers Operating Company 3. Address of Operator 2700 Framington Ave. Bldg. K. Ste 1 Farmington, NM 87401 9. Pool name or Wildcat Basin Dakota / Blanco Mesaverde 4. Well Location Unit Letter M. 1,050 Feet From The South Line and 870 Feet From The West Line Section 16 Township 30N Range 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5667' Ground Level 11. Check Appropriate Box to Indicate NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPNS. ALTERING CASING CHANGE PLANS CASING TEST AND CEMENT JOB OTHER: 12. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propowordy) SEE RULE 1103. Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information abovy is trye and complete to the best of my knowledge and bellef.  SICNATURE TITLE Drilling Engineer DATE 11/28/00		J OTHER	1991	C 547-11 N		
3. Address of Operator 2700 Farmington Ave., Bldg, K. Ste 1 Farmington, NM 87401  4. Well Location Unit Letter M: 1.050 Feet From The South Line and 870 Feet From The West Line section 16 Township 30N Range 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, etc.)  10. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE TEAT AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations/Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportion works) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2' casing at 6.953' KB. The casing was cemented in two stages using a total 1.250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.  Thereby certify that the information abovy is trye and complyte to the best of my knowledge and belief.	-	nany		I .		
4. Well Location Unit Letter M: 1,050 Feet From The South Line and 870 Feet From The West Line    Section 16	3. Address of Operator	•	87401	9. Pool name or V		esaverde
10. Elevation (Show whether DF, RKB, RT, GR, etc.)   5667   Ground Level   11.   Check Appropriate Box to Indicate   Nature of Notice, Report, or Other Data   NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:   ALTERING CASING   COMMENCE DRILLING OPNS.   ALTERING CASING   COMMENCE DRILLING OPNS.   PLUG AND ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   PLUG AND ABANDONMENT   COMMENCE DRILLING OPNS.   CASING TEST AND CEMENT JOB   OTHER:						
10. Elevation (Show whether DF, RKB, RT, GR, etc.)  11. Check Appropriate Box to Indicate  NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   ALTERING CASING    TEMPORARILY ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   PLUG AND ABANDONMENT    PULL OR ALTER CASING   OTHER:   OTHER:   OTHER:    12. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propowork) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE   Drilling Engineer   DATE   11/28/00	Ι u 1 Δ	50 Feet From The South	Line and 87	Feet Fron	The We	est Line
10. Elevation (Show whether DF, RRB, RT, GR, etc.) 5667' Ground Level  11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT  12. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proport work) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6.958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6.953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE TIME Drilling Engineer DATE 11/28/00	Section 16	1077102110	THE COURT OF THE C		San Juan	County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. ALTERING CASING COMMENCE DRILLING OPNS. DLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations/Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propowork) SEE RULE 1103.  13. Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SECNATURE Drilling Engineer DATE 11/28/00		10. Elevation (Show who		c.)		
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT  CASING TEST AND CEMENT JOB  OTHER:  12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposor  or the well . On 11/25/00 Cross Timbers set 165 jts of 4·1/2" casing at 6.953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  NENATURE Drilling Engineer DATE 11/28/00	11. Check A			ice, Report, o	r Other D	ata
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. DELIG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportion of the Well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE Drilling Engineer DATE 11/28/00						
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportion work). SEE RULE 1103.  13. Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE Drilling Engineer DATE 11/28/00						
PULL OR ALTER CASING  OTHER:  12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportions of the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6.953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SICNATURE  TITLE Drilling Engineer  DATE 11/28/00	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	F	ALTERING CA	SING $\square$
OTHER:  12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proportion work) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE  Drilling Engineer  DATE 11/28/00	TEMPORARILY ABANDON	CHANGE PLANS L_	COMMENCE DRILLING	G OPNS.	PLUG AND AB	ANDONMENT L
12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proporation of the well. SERULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6.953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE Drilling Engineer DATE 11/28/00	PULL OR ALTER CASING		CASING TEST AND CI	EMENT JOB		
12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propowork) SEE RULE 1103.  Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE	OTHER:		OTHER:			
Cross Timbers Operating Co. reached a total depth of 6,958' KB on 11/23/00. Open hole logs were ran on the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE  TITLE Drilling Engineer  DATE 11/28/00		0 (01 1 11				
the well. On 11/25/00 Cross Timbers set 165 jts of 4-1/2" casing at 6,953' KB. The casing was cemented in two stages using a total 1,250 sx (2,615 cuft) of cement. Cement was circ to the surface on both stages. After the casing was cemented the slip were set, the casing was cut off and the drilling rig was released.  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE  TITLE Drilling Engineer  DATE 11/28/00		OperationsClearly state all pertinent	details, and give pertinent	dates, including es	dimated date of	starting any propos
SIGNATURE Drilling Engineer DATE 11/28/00	the well. On 11/25/00 in two stages using a stages. After the cas	Cross Timbers set 165 jts total 1,250 sx (2,615 cuft)	of 4-1/2" casing at of cement. Cement	: 6,953' KB. T : was circ to t	The casing w the surface	was cemented on both
SIGNATURE Drilling Engineer DATE 11/28/00						
SIGNATURE Drilling Engineer DATE 11/28/00						
SIGNATURE Drilling Engineer DATE 11/28/00						
SIGNATURE Drilling Engineer DATE 11/28/00						
SIGNATURE Drilling Engineer DATE 11/28/00						
SIGNATURE Drilling Engineer DATE 11/28/00	I hereby certify that the information abov	e is true and complete to the best of my kno	owledge and belief.		· ···	
TELEPHONE NO. 324-1000	$\mathcal{A}$	11117		eer	DATE	11/28/00
TYPE OR PRINT NAME JW POLLUTI	TYPE OR PRINT NAME JW Patton				TELEPHONE NO.	324-1090

GREENAL SIGNED BY CHARLIE T. PERMIN

(This space for State Use)