Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FØRM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

Lease Designation and Serial No.

SF-078138

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals
Use "APPLICATION FOR PERMIT—" for such proposals

6. If Indian, Allottee or Tribe Name

NA

SUBMIT IN T	RIPLICATE	NA
1. Type of Well Oil Well X Gas Well Other		8. Well Name and No. Carle 2B
Name of Operator Koch Exploration Company		9. API Well No. 30-045-30369
3. Address and Telephone No. P.O. Box 489 Aztec, New Mexico 8		10. Field and Pool, or Exploratory Area Blanco Mesa Verde
4. Location of Well (Footage, Sec., T., R., M., or Survey D S20, T30N, R11W (H) 1885' FNL & 965' FEL	JAN 2001 C DINDICATE NATURE OF NOTICE,	11. County or Parish, State San Juan County New Mexico REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF	ACTION
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
X Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing X Other Run Casing & Cement	Conversion to Injection Dispose Water
	A one run casing a commit	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Compelted Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 6 1/4" hole, ran 4 1/2", 10.5#, J-55 new casing from surface and landed @ 4891' KB. KB= 13'0". 7", 23#, J-55 new casing @ 2529' KB. Cemented on 12/2/00, lead with 50 sacks of 10.5#, Yield 4.16 Premium Lite Type III cement (35:65) Poz L + 10#/sack CSE + 1/4# /sack Cello Flake. Tailed with 148 sacks of 12.0#, Yield 2.38 Premium Lite Type III cement (35:65) Poz L +10#/sack CSE + 3% Potassuim Chloride + 1/4# / sack Cello Flake + 5# / sack LCM-1. WOC 96 Hours. Ran CBL log on 12/6/00 and TOC @ 1990'. Pressure Tested Casing on 12/13/00 to 3850# for 30 minutes, Held OK.

hereby certify that the foregoing is true and correct		
igned This space for Pederal or Signe office use)	Title Operations Manager	ACCEPTED ADOR R
pproved by	Title	Date
V	wingly and willfully to make to any department or agency of the Un.	FARMINGTON FIELD