

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No.

SF-081089

6. If Indian, Allottee or Tribe Name

7. Unit or C/A Agreement, Name and/or No.

San Juan 32-8 Unit

8. Well Name and No.

SJ 32-8 Unit #1A

9. API Well No.

30-045-30411

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other

4-1/2" casing

report

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

RIH w/6-1/4" bit & tagged cement @ 2878'. Drilled out cement from 2878' to 2954'. Drilled new formation to TD @ 6065'. TD reached 4/3/01. Circ. hole. RIH w/4-1/2" 11.6#, J-55 casing, unable to get past 6039'. Set @ 6039' with ECP set @ 5190' and DV tool set @ 5182'. RU to cement. Pumped 10 bbls FW, 10 bbls gel water, 10 bbls FW w/red dye ahead of 1st stage Lead - 45 sx (95.5 cf - 17 bbl slurry) Type 3 35/65 POZ w/6% gel, 10#/sc CSE, 0.02#/sx Static Free, 0.75% FL-52, 0.2% CD-32, 1/4#/sx Cello-flake. Pumped tail - 20 sx (30.9 cf - 5.5 bbl slurry) Type 3 cement 35/65 POZ w/6% gel, 10#/sx CSE, 0.02#/sx Static Free, 0.75% FL-52, 0.2% CD-32, 1/4#/sx Cello-flake. Dropped plug and displaced w/91.5 bbls FW. Bumped plug @ 500#. Inflated ECP. Opened DV tool.

Pumped 2nd stage. Pumped 10 bbl water spacer w/red dye ahead of Lead - 130 sx (308.8 cf - 55 bbl slurry) Type 3 cement 35/65 POZ w/6% gel, 3% KCl, 0.4% FL-25, 5#/sx LCM-1, 1/4#/sx Cello-flake, 10#/sx CSE, 0.02#/sx Static Free. Tail - pumped 50 sx (67.4 cf - 12 bbl slurry) Type 3 cement w/1/4#/sx Cello-flake & 1% CaCl2. Dropped plug & displaced w/80.5 bbls FW. Plug down @ 1245 4/4/01. Bumped plug w/1600#. Held good. WOC. ND BOP, set slips and cut off casing. RD & released rig 4/4/01 @ 1600 hrs.

Will show PT and TOC on next report.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Patsy Clugston

Title

Sr. Regulatory/Proration Clerk

Date

4/5/01

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

APR 13 2001

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

FEDERAL FIELD OFFICE