Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5 . I	Lease	Serial	No.
--------------	-------	--------	-----

SIMPLY NOTICES	AND REPORTS ON 1	NEW 13 14 15 16	75	NM-012641		
Do not use this form for	proposals to drill or to re-en			6. If Indian, Allottee or Tribe Name		
abandoned well. Use For	m 3160-3 (APD) for such p	Seals. APR 200				
		O CE V	2	7. If Unit or CA/Agreement, Name and/or No.		
SUBMIT IN TRIPLICATE -	<u> </u>	Plance				
1. Type of Well Oil Well X Gas Well Other	f.			8. Well Name and No.		
2. Name of Operator	<u> </u>					
Phillips Petroleum Company				Blanco #10A 9. API Well No.		
3a. Address	rea code)	30-045-30413				
5525 Highway 64, NBU 3004, Farmingt		10. Field and Pool, or Exploratory Area				
 Location of Well (Footage, Sec., T., R., M., or Survey Unit C, 1039' FNL & 1453' FWL 		Blanco Mesaverde				
Section 26, T31N, R8W		11. County or Parish, State				
		San Juan NM				
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Intent	Acidize	Deepen	Production	n (Start/Resume) Water Shut-Off		
	Alter Casing	Fracture Treat	Reclamation	on Well Integrity		
X Subsequent Report	Casing Repair	New Construction	Recomple	te Other		
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporar	ily Abandon NTL-FRA-90-1		
Final Abandonment Nonce	Convert to Injection	Plug Back	Water Dis			
Description of cement job to fulfill required including the Ojo Alamo Formation, as Date: 3/20/01 Time Started: 00 Hole: 8-3/4" Casing Size: 7", Turbo Centralizers at 2165', 2122',	<u>s</u> _ft.	2001 HAR 2				
Spring Type Centralizers 2975', _ Mud Flush 10 bbls, Spacer 40 bbls	<u>, 310°</u> ,	©3				
Stone 1: Lead Shurry: 20 sy (28 cf) Tyl						
Stage 2: Lead = 400 sv (954.5 cf) Type	7.7					
Flake, 5#/sx LSM-1, 10#/sx CSE, 3% KCl, 0.4% FL-25 & 0.02#/sx Static free. Tail – 80 sx (112.3cf) Class H w/75% FL-62, 0.2% CD-32, 0.2% Metalisilicate, 5#/sx						
I CM & 1/4#/sy Cello-flake						
Volume Cement Circulated 1 bbls to surface. Displaced Plug with 112.8 bbl FW. Average Pressure 280 #, Average Rate 4.7 bpm, Bumped plug with 2125 psi.						
14. I hereby certify that the foregoing is true and correct		Title				
Name (Printed/Typed) Patsy Clugston Sr. Regulatory/Proration (//Proration Clerk		
False (flex)		Date 3/23,	/01	200		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
		Title		Date 9 2001		
Approved by				APR 1 3 ZUUI		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.				FATMINGTON FIELD OFFICE		
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section States any false, fictitious or fraudulent statements or represent	on 1212, makes it a crime for tations as to any matter within it	r any person knowingly ts jurisdiction.	and willfully to 1	nake to any department or gency of the United		