

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-045-30545

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

Lease Name or Unit Agreement Name:

McKenzie "A"

8. Well No.

#2

9. Pool name or Wildcat

Basin FC & Aztec PC

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG OR ABANDON A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM 3301) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Cross Timbers Operating Company

3. Address of Operator

2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401

4. Well Location

Unit Letter B : 1,110 feet from the North line and 1,790 feet from the East line

Section 9 Township 30N Range 12W NMPM County San Juan

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

5,775' Ground Level

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Cross Timbers Operating Co. (now known as XTO Energy) spudded an 8-3/4" hole on 6/27/01. Drilled to a depth of 215' KB. Ran 12 jts 7", 20#, J-55 casing to a depth of 215' KB. Cemented casing with 60 sx cl "B" cement w/2% CaCl2 & 1/4#/sx celloflake. Circ 6 bbls cement to the surface.

Installed and PRESSURE TESTED the SURFACE CASING AND BOP's to 1,000 psig for 30 minutes. Held OK.

Resumed drilling on 6/28/01.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jeffrey W. Patton TITLE Drilling Engineer DATE 6/29/01

Type or print name Jeffrey W. Patton Telephone No. 324-1090

(This space for ORIGINAL SIGNATURE)

APPROVED BY Jeffrey W. Patton TITLE Drilling Engineer DATE JUL -5 2001

Conditions of approval, if any: