

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

## 1. Type of Well

GAS

## 2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL &amp; GAS COMPANY

## 3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

## 4. Location of Well, Footage, Sec., T, R, M

1605'FNL, 2560'FWL, Sec.7, T-30-N, R-10-W, NMPM

## 5. Lease Number

NM-03195-A

## 6. If Indian, All. or

Tribe Name

## 7. Unit Agreement Name

## 8. Well Name &amp; Number

Sullivan #1B

## 9. API Well No.

30-045-30566

## 10. Field and Pool

Blanco MV/Basin DK

## 11. County and State

San Juan Co, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☒ Notice of Intent☐ Abandonment☒ Change of Plans☐ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☒ Other -

## 13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well as follows:

## Mud Program:

Interval	Type	Weight	Vis	Fluid Loss
0- 320'	Spud	8.4-9.0	40-50	no control
320- 4709'	LSND	8.4-9.0	30-60	no control
4709- 7325'	Air/N2	n/a	n/a	n/a

## Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0' - 320'	9 5/8"	32.3#	WC-50
8 3/4"	0' - 4709'	7"	20/23#	J55/N80
6 1/4"	4609' - 7325'	4 1/2"	10.5#	K-55

## Cementing Program:

9 5/8" surface casing - cement with 255 sx Class "B" cement with 0.25# flocele, and 3% calcium chloride (301 cu.ft. of slurry, 200% excess to circulate to surface).

7" intermediate casing - Lead w/595 sx 50/50 Class G/TXI lightweight w/1.75% sodium metasilicate, 0.2% defoamer, 8# gilsonite, 0.15% retarder and 1/2# flocele. Tail w/95 sx 50/50 Class "G" Poz w/2% gel, 0.25 pps flocele, 5 pps gilsonite, 0.1% defoamer, 0.1% dispersant, 0.1% retarder (1417 cu.ft. of slurry, 100% excess to circulate to surface.)

7" alternative two stage - Stage tool set @ 2099'. Stage #1 w/623 sx 50/50 Class "G" Poz w/2% gel, 0.25 pps celloflake, 5 pps gilsonite, 0.1% defoamer, 0.1% dispersant, 0.1% retarder. Stage #2 w/290 sx 50/50 Class G/TXI lightweight w/1.75% sodium metasilicate, 0.2% defoamer, 10# gilsonite, 0.15% retarder, 0.25# flocele/sx (1417 cu.ft. of slurry, 100% excess to circ to sur).

4 1/2" production liner - Lead with 271 sx 50/50 Class "G" Poz w/5% gel, 0.25# flocele, 5# gilsonite, 0.1% retardant, 0.15% TIC dispersant, 0.1% antifoam agent and 0.25% fluid loss additive (390 cu.ft., 40% excess to cement 4 1/2" x 7" overlap).

## 14. I hereby certify that the foregoing is true and correct.

Signed Shawn Call Title Regulatory Supervisor Date 12/5/01

TLW

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date 12/14/01

## CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC