

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a TYPE OF WORK DRILL ☒ DEEPEN ☐

b TYPE OF WELL OIL WELL ☐ GAS WELL ☒ OTHER ☐ SINGLE ZONE ☐ MULTIPLE ZONE ☒

2 NAME OF OPERATOR AMOCO PRODUCTION COMPANY
P.O. BOX 3092
HOUSTON, TX 77079

3 ADDRESS AND TELEPHONE NO. MARY CORLEY
AUTHORIZED REPRESENTATIVE
PHONE 281.366.4491 EXT: 281.366.0400
FAX: 281.366.0400
EMAIL: corleym@bp.com

4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
At Surface 1080FNL AND 2385FWL NENW SEC 21 T30N R9W
At proposed prod. zone

5 LEASE DESIGNATION AND SERIAL NO. SF - ~~07816~~ 080244

6 IF INDIAN, ALLOTTEE OR TRIBE NAME

7 UNIT AGREEMENT NAME

8 FARM OR LEASE NAME, WELL NO. RIDDLE 1M

9 API WELL NO. 30-045-30626

10 FIELD AND POOL, OR WILDCAT BASIN DAKOTA/BLANCO MESAVERDE

11 SEC., T., R., M., OR BLK. AND SURVEY OR AREA SECTION 21 T30N R9W
MERIDIAN NMP

12 COUNTY OR PARISH SAN JUAN

13 STATE NM

14 DISTANCE IN MILES AND DIRECTION FROM THE NEAREST TOWN OR POST OFFICE 12 MILES FROM AZTEC

15 DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any)

16 NO. OF ACRES IN LEASE 320.00

17 NO. OF ACRES ASSIGNED TO THIS WELL 320.00

18 DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE FT.

19 PROPOSED DEPTH 7383 MD / TVD

20 ROTARY OR CABLE TOOLS ROTARY

21 ELEVATIONS (Show whether DF, RT, GR, etc.) 5959 GL

22 APPROX. DATE WORK WILL START* 05/20/2001

23. PROPOSED CASING AND CEMENTING PROGRAM				
SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT

Notice of Staking Submitted 12/07/2000. Amoco Production Company respectfully request permission to drill the subject well to a total depth of approximately 7383', complete in the Basin Dakota Pool, produce the well for approximately 30 days to establish production rate, add the Blanco Mesaverde Pool and commingle production downhole. Application for downhole commingling authority (NMOCD order R-11363) will be submitted to all appropriate parties for approval after production has been established in the Basin Dakota Pool and prior to completion of and downhole commingling with the Blanco Mesaverde. Please see attached documents in support of our application

THIS APPLICATION IS FOR A PERMIT TO DRILL OR DEEPEN A WELL TO A TOTAL DEPTH OF 7383' AND A PROPOSED DEPTH OF 7383' TO A TOTAL DEPTH OF 7383' AND A PROPOSED DEPTH OF 7383' TO A TOTAL DEPTH OF 7383'.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. ELECTRONIC SUBMISSION #3561 VERIFIED BY THE BLM WELL INFORMATION SYSTEM
FOR AMOCO PRODUCTION COMPANY SENT TO THE FARMINGTON FIELD OFFICE

SIGNED MARY CORLEY TITLE AUTHORIZED REPRESENTATIVE DATE 04/10/2001

PERMIT NO. APPROVAL DATE 6/8/01

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY /s/ Lee Otter TITLE DATE

District I
PO Box 1980, Hobbs NM 88241-1980
District II
PO Drawer KK, Artesia, NM 87211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994

Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-045-30626		² Pool Code 71599 & 72319	³ Pool Name BASIN DAKOTA & BLANCO MESAVERDE
⁴ Property Code 00971	⁵ Property Name RIDDLE		⁶ Well Number # 1M
⁷ OGRID No. 00778	⁸ Operator Name AMOCO PRODUCTION COMPANY		⁹ Elevation 5959

¹⁰ Surface Location


UL or Lot No. C	Section 21	Township 30 N	Range 9 W	Lot Idn	Feet from the 1080	North/South line NORTH	Feet from the 2385	East/West line WEST	County SAN JUAN
--------------------	---------------	------------------	--------------	---------	-----------------------	---------------------------	-----------------------	------------------------	--------------------

¹¹ Bottom Hole Location If Different From Surface

¹ UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 320.00		¹³ Joint or Infill		¹⁴ Consolidation Code		¹⁵ Order No.			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p>¹⁷ OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Mary Corley</i> Signature MARY CORLEY Printed Name SR. REGULATORY ANALYST Title 04-09-2001 Date</p>
	<p>¹⁸ SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>November 16, 2000 Date of Survey Signature and Seal of Professional Surveyor <i>GARY D. JENN</i> 7016 Certificate Number</p>



**AMOCO
PRODUCTION COMPANY**

**Riddle # 1B
NW¼ Section 21,
T30N, R9W, N.M.P.M.**

150' New BLM Road Construction

NE¼NW¼

APD MAP # 1

**AMOCO PRODUCTION COMPANY
DRILLING AND COMPLETION PROGRAM**

Prospect Name: Riddle
Lease: RIDDLE
County: San Juan
State: New Mexico
Date: April 10, 2001

Well No: 1M
Surface Location: 21-30N-9W, 1080 FNL, 2385 FWL
Field: Blanco Mesaverde/Basin Dakota

OBJECTIVE: Drill 400' below the base of the Greenhorn Limestone, set 4" Liner across Dakota, Stimulate LS, CH, MF, PL and DK intervals

METHOD OF DRILLING		APPROXIMATE DEPTHS OF GEOLOGICAL MARKER			
TYPE OF TOOLS	DEPTH OF DRILLING	Estimated GL: 5959		Estimated KB: 5973	
Rotary	0 - TD	MARKER		SUBSEA	MEAS. DEPTH
LOG PROGRAM		Ojo Alamo		4622	1351
TYPE	DEPTH INVERAL	Fruitland Coal	*	3851	2123
<u>OPEN HOLE</u>		Pictured Cliffs	*	3297	2676
GR-Induction	TD to 5 1/2" shoe	Lewis Shale	#	3228	2745
Density/Neutron	TD to 5 1/2" shoe	Cliff House	#	1660	4314
Sonic	TD to 5 1/2" shoe	Menefee Shale	#	1482	4491
<u>CASED HOLE</u>		Point Lookout	#	1045	4928
GR-CCL-TDT	TDT - PBDT-7 5/8" shoe	Mancos		950	5024
	GR-CCL - PBDT-0'	Greenhorn		-946	6919
CBL	Top of 4" - 50' above 7 5/8" shoe	Bentonite Marker		-1010	6983
REMARKS:		Two Wells	#	-1052	7025
- Please report any flares (magnitude & duration).		Dakota MB	#	-1190	7163
		Burro Canyon	*	-1365	7338
		Morrison	*	-1415	7388
		TOTAL DEPTH		-1410	7383
		# Probable completion interval		* Possible Pay	
SPECIAL TESTS		DRILL CUTTING SAMPLES		DRILLING TIME	
TYPE		FREQUENCY	DEPTH	FREQUENCY	DEPTH
None		10 feet	Production hole	Geolograph	0-TD
REMARKS:					

MUD PROGRAM:							
Approx. Interval			Type Mud	Weight, #/gal	Vis, sec/qt	W/L cc's/30 min	Other Specification
0	-	120-135	3 jts.	Spud	8.6-9.2		
120-135	-	2073	(1)(2)	Water/LSND	8.6-9.2		
2073	-	6983		Gas/Air/Mist	Volume sufficient to maintain a stable and clean wellbore		
6983		7383		LSND	8.6-9.2		

REMARKS:
(1) The hole will require sweeps to keep unloaded while fresh water drilling. Let hole conditions dictate frequency.
(2) Top set Fruitland Coal to minimize lost circulation, air volume to maintain hole stability.

CASING PROGRAM: (Normally, tubular goods allocation letter specifies casing sizes to be used. Hole sizes will be governed by Contract)

Casing String	Estimated Depth	Casing Size	Grade	Weight	Hole Size	Landing Pt, Cmt, Etc.
Surface/Conductor	120-135	10 3/4"	J-55 ST&C	40.5#	14.75"	1 —
Intermediate 1	2073	7 5/8"	K-55 LT&C	26.4#	9.875"	1,2 —
Intermediate 2	6983	5 1/2"	K-55 LT&C	15.5#	6.75"	4)
Production (liner)	7383	4"	K-55 H 511	11#	4.75"	3 —

REMARKS:
(1) Circulate Cement to Surface
(2) Set casing 50' above Fruitland Coal
(3) Liner Lap should be a minimum of 100'
(4) Bring cement 200' above 7 5/8" shoe

CORING PROGRAM:

None

COMPLETION PROGRAM:

Rigless, 4-6 Stage Limited Entry Hydraulic Frac

GENERAL REMARKS:

Notify BLM/NMOCD 24 hours prior to Spud, BOP testing, and Casing and Cementing.

Form 46 Reviewed by: Logging program reviewed by: N/A

PREPARED BY:	APPROVED:	DATE:	
KAS/KAT		January 5, 2001	
Form 46 12-00 KAT		Version 1.0	

Cementing Program: RIDDLE 1M

	Surface	Intermediate	I2	Liner
Excess %, Bit	100%	80	50	10
Excess %, Caliper	NA	NA	NA	30
BHST (est deg. F)	60	120	150	160
Pipe Movement	NA	Rotate/Reciprocate	Rotate/Reciprocate	as per Liner Co.
Rate, Max (bpm)	7	4	4	2
Rate Recommended (bpm)	6	4	3	2
Pressure, Max (psi)	200	2000	2000	2000
Shoe Joint	40	80	80	40
Batch Mix	NA	NA	NA	NA
Circulating prior cmtng (hr)	0.5	1.5	2.5	2
Time Between Stages, (hr)	NA	NA	NA	NA
Special Instructions	1,6,7	1,6,8	1,6,9	2,3,4,6

1. Do not wash pumps and lines.
2. Wash pumps and lines.
3. Reverse out
4. Run Blend Test on Cement
5. Record Rate, Pressure, and Density on 3.5" disk
6. Confirm densitometer with pressurized mud scales
7. 1" cement to surface if cement is not circulated.
8. If cement is not circulated to surface, run temp. survey 10-12 hr. after landing plug.

Notes:

- *Do not wash up on top of plug. Wash lines before displacing liner cement job to minimize drillout.
- ** After cement set time the liner top will be drilled out and liner circulated clean with treated water.
- *** Run TMD cased hole logs to identify pay; Perforating and CH logs can be run rigless.

Surface:

Preflush	20 bbl.	FreshWater	
Slurry 1	120sx Class G Cement		139cuft
TOC@Surface	+ 2% CaCl ₂ (accelerator)		
	0.25 #/sk Cellophane Flake (lost circulation additive)		0.5563cuft/ft OH
	0.1% D46 antifoam		100% excess
Slurry Properties:	Density	Yield	Water
	(lb/gal)	(ft ³ /sk)	(gal/sk)
Slurry 1	15.8	1.16	4.95
Casing Equipment:	10-3/4", 8R, ST&C		
	1 Guide Shoe		
	1 Top Wooden Plug		
	1 Autofill insert float valve		
	4 Centralizers		
	1 Stop Ring		
	1 Thread Lock Compound		

Cementing Program: RIDDLE 1M

Intermediate:				
Fresh Water	20 bbl	fresh water		
Lead	208sx	Class "G" Cement	605 cuft	
Slurry 1		+ 3% D79 extender		
TOC@Surface		+ 2% S1 Calcium Chloride		
		+1/4 #/sk. Cellophane Flake		
		+ 0.1% D46 antifoam'		
Tail	152sx	50/50 Class "G"/Poz	1931 cuft	
Slurry 2		+ 2% gel (extender)		
	500ft fill	0.1% D46 antifoam	0.2148 cuft/ft OH	
		+1/4 #/sk. Cellophane Flake	0.2338 cuft/ft csg ann	
		+ 2% CaCl2 (accelerator)	80 % excess	
Slurry Properties:				
	Density	Yield	Water	
	(lb/gal)	(ft3/sk)	(gal/sk)	
Slurry 1	11.4	2.9	17.77	
Slurry 2	13.5	1.27	5.72	
Casing Equipment:				
	7-5/8", 8R, ST&C			
	1 Float Shoe (autofill with minimal LCM in mud)			
	1 Float Collar (autofill with minimal LCM in mud)			
	1 Stop Ring			
	9 Centralizers (one in middle of first joint, then every third collar)			
	2 Fluidmaster vane centralizers @ base of Ojo			
	8 Centralizers one every 4th joint from Ojo to base of surface casing			
	1 Top Rubber Plug			
	1 Thread Lock Compound			

Int 2:				
Fresh Water	10 bbl	CW100		
Lead	487	LiteCrete D961 / D124 / D154	1043 cuft	
Slurry 1		+ 0.03 gps D47 antifoam		
TOC@Surface		+ 0.5% D112 fluid loss		
		+ 0.11% D65 TIC		
Tail	80sx	50/50 Class "G"/Poz	115 cuft	
Slurry 2		+ 5% D20 gel (extender)	+ 5 #/sk D24 gilsonite	
	500ft fill	+ 0.1% D46 antifoam	+ 0.15% D65 TIC	
		+ 1/4 #/sk. Cellophane Flake	+ 0.1% D800 retarder	
		+ 0.25% D167 Fluid Loss		
			0.1521 cuft/ft OH	
Slurry Properties:				
	Density	Yield	Water	
	(lb/gal)	(ft3/sk)	(gal/sk)	
Slurry 1	9.5	2.14	6.38	
Slurry 2	13	1.44	6.5	
Casing Equipment:				
	5-1/2", 8R, ST&C			
	1 Float Shoe (autofill with minimal LCM in mud)			
	1 Float Collar (autofill with minimal LCM in mud)			
	1 Stop Ring			
	35 Centralizers (every third joint)			
	1 Top Rubber Plug			
	1 Thread Lock Compound			

Cementing Program: RIDDLE 1M

Production (liner):

Preflush	10 bbl.	CW100 / LCM wash	
Lead Cement		2350/50 Poz/G	34 cuft
Slurry 1		5% D20 bentonite	0.1% D46 antifoam
	100ft lap	0.25#/sk D29 cellophane	
	100ft cap	0.25% D167 Fluid loss	0.0358 cuft/ft OH
		0.15% D65 TIC	0.0464 cuft/ft csg ann
		0.15% D800 retarder	0.1336 cuft/ft csg
Slurry Properties:	Density	Water	10 % excess
	(lb/gal)	(ft3/sk)	(gal/sk)
Slurry 1	13	1.44	6.5

Liner Float Equipment:

Float Shoe and Float Collar (furnished by Liner Hanger Company)
1 Thread Lock Compound

Note:

1. Coordinate w/Liner hand to drop plug, or set/release Liner as required
2. The job should be pumped at 2-3 bpm max rate. Do not exceed 3 bpm on displacement
3. Wash pump and lines before displacement. Slow to 1 bpm for the last 30 bbl of displacement.
4. This is to be a rigless completion. After cement set time, liner top will be dressed off an liner circulated clean with 2 % KCl or 2 gal/1000 gal L64.

FEDERAL CEMENTING REQUIREMENTS

1. All permeable zones containing fresh water and other usable water containing 10,000 PPM or less total dissolved solids will be isolated and protected from contamination by cement circulated in place for the protection of permeable zones per the NTL-FRA 90-1 Section III A.
2. The hole size will be no smaller than 1 ½" larger diameter than the casing O.D. across all water zones.
3. An adequate spacer will be pumped ahead of the cement slurry to help prevent mud contamination of the cement.
4. An adequate number of casing centralizers will be run through usable water zones to ensure that the casing is centralized through these zones. The adequate number of centralizers to use will be determined by API SPEC 10D.
5. Centralizers will impart a swirling action around the casing and will be used just below and into the base of the lowest usable water zone.
6. A chronological log will be kept recording the pump and slurry information and will be sent to the BLM with the subsequent sundry.

**Amoco Production Company
BOP Pressure Testing Requirements**

Well Name: RIDDLE 1M

County: San Juan

State: New Mexico

Formation	TVD	Anticipated Bottom Hole Pressure	Maximum Anticipated Surface Pressure **
Ojo Alamo	1351		
Fruitland Coal	2123		
PC	2676		
Lewis Shale	2745		
Cliff House	4314	500	0
Menefee Shale	4491		
Point Lookout	4928	600	0
Mancos	5024		
Dakota	7025	2600	1495

** Note: Determined using the following formula: $ABHP - (.22 * TVD) = ASP$

Requested BOP Pressure Test Exception: 3000 PSI

**SAN JUAN BASIN
Dakota Formation
Pressure Control Equipment**

Background

The objective Dakota formation maximum surface pressure is anticipated to be less than 1000 PSI, based on shut-in surface pressures from adjacent wells. Pressure control equipment working pressure minimum requirements are therefore 2000 PSI. Equipment to be used will conform to API RP-53 (Figure 2.C.2) for a 2000 PSI system per Federal Onshore Order No. 2. Due to available conventional equipment within the area, 3000 PSI rated pressure control equipment will typically be utilized in a double ram type arrangement. Regional drilling rights to be utilized have substructure height limitations which exclude the use of annular preventers; therefore a rotating head will be installed above these rams. This pressure control equipment will be utilized for conventional drilling below conductor to total depth in the Basin Dakota. No abnormal temperature, pressure, or H2S anticipated.

Equipment Specification

Interval

BOP Equipment

Below conductor casing to total depth

11" nominal or 7 1/16", 3000 PSI
double ram preventer with rotating
head.

All ram type preventers and related control equipment will be hydraulically tested to 250 PSI (low pressure) and 2000 PSI (high pressure), upon installation, following any repairs or equipment replacements, or at 30 day intervals. Accessories to BOP equipment will include kelly cock, upper kelly cock with a handle available, floor safety valves and choke manifold which will also be tested to equivalent pressure.