

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0135
Expires: January 31, 2004**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

NMNM-0207001

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA/Agreement, Name and/or No.

56

N/A

8. Well Name and No.

WF Federal 25 #2

9. API Well No.

30-045-30713

10. Field and Pool, or Exploratory Area

Harper Hill PC Ext

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other See below

3. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleting horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleting in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

9-26-02 Spud 8 3/4" surface hole. Drill to 50'. SDFN

9-27-02 Drill to 129'. Ran 4 jts. 7" 17# casing; set at 125.55' KB. Cemented with 60 sx (71 cf) Class 'B' w/ 2 % CaCl₂ 1/4#/sk celloflake. Circ. 5 Bbl cement to pit. WOC 12 hours.

9-28-02 Install and test BOP to 600 psi, 30 min; test good. Test surface casing to 600 psi, 30 min; test good. Drill 6 1/4" hole to 450'. SDFN

9-30-02 Drill 6 1/4" hole to 1250'. SDFN

10-01-02 Drill 6 1/4" to 1330'; TD. Tally and run 31 joints 4.5" K-55 10.5# casing; set guide shoe at 1329.72' KB. Cemented with 61 sx (126 cf) Class 'B' with 2% metasilicate, 1/4# celloflake and 65 sx (77 cf) Class 'B' with 2 % CaCl₂. Bumped plug to 1000 psi. Circ. 7 Bbl cmt to surface.

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Drew Carnes

Title Operations Manager

Signature

Date 10-7-02

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

ACCEPTED FOR RECORD

Approved by (Signature)

Name
(Printed/Typed)

Title 15 2002

Office

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on next page)

NMCCD