

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0136
Expires November 30, 2000

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMSF - 078387-A	
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name	
2. Name of Operator AMOCO PRODUCTION COMPANY Contact: MARY CORLEY E-Mail: corleyml@bp.com		7. If Unit or CA Agreement, Name and No.	
3a. Address P.O. BOX 3092 HOUSTON, TX 77253		8. Lease Name and Well No. FLETCHER 1M	
3b. Phone No. (include area code) Ph: 281.366.4491 Fx: 281.366.0700		9. API Well No. 30-045-30767	
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface SENW Lot F 2310FNL 1540FWL 36.51300 N Lat, 107.41000 W Lon At proposed prod. zone		10. Field and Pool, or Exploratory BASIN DAKOTA/BLANCO MESAVERDE	
14. Distance in miles and direction from nearest town or post office* 22 MILES FROM AZTEC, NM		11. Sec., T., R., M., or Blk. and Survey or Area F Sec 33 T31N R8W Mer NMP	
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1540		12. County or Parish SAN JUAN	
16. No. of Acres in Lease 8060 MD		13. State NM	
18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.		17. Spacing Unit dedicated to this well 320 u/2	
21. Elevations (Show whether DF, KB, RT, GL, etc.) 6447 GL		20. BLM/BIA Bond No. on file	
22. Approximate date work will start 09/01/2001		23. Estimated duration	

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature	Name (Printed/Typed) MARY CORLEY	Date 07/27/2001
Title AUTHORIZED REPRESENTATIVE		
Approved by (Signature) <i>[Signature]</i>	Name (Printed/Typed)	Date 11/26/01
Title AFM	Office FFO	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #6015 verified by the BLM Well Information System
For AMOCO PRODUCTION COMPANY, sent to the Farmington
Committed to AFMSS for processing by Maurice Johnson on 08/02/2001 ()

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4.

UNLAWFUL OVERLAP OF INTERESTS ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS"

** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL **

WOLD C104 FOR NSL - Basin Dakota

NMSF

K

District I
PO Box 1980, Hobbs NM 88241-1980
District II
PO Drawer KK, Artesia, NM 87211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-045-30767	² Pool Code 71599 ? 72319	³ Pool Name BASIN DAKOTA ? BLANCO MESA VERDE
⁴ Property Code 000517	⁵ Property Name Fletcher	⁶ Well Number # 1M
⁷ OGRID No. 000 778	⁸ Operator Name AMOCO PRODUCTION COMPANY	⁹ Elevation 6447



¹⁰ Surface Location

UL or Lot No. F	Section 33	Township 31 N	Range 8 W	Lot Idn	Feet from the 2310	North/South line NORTH	Feet from the 1540	East/West line WEST	County SAN JUAN
---------------------------	----------------------	-------------------------	---------------------	---------	------------------------------	----------------------------------	------------------------------	-------------------------------	---------------------------

¹¹ Bottom Hole Location If Different From Surface

⁷ UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 320	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<div></div>	<div><p>17 OPERATOR CERTIFICATION</p><p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p><p><i>Mary Giley</i> Signature MARY GILEY Printed Name Sr Regulatory Analyst Title 7-27-01 Date</p><p>18 SURVEYOR CERTIFICATION</p><p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p><p>May 14, 2001 Date of Survey</p><p><i>Gray D. Givins</i> Signature and Seal of Professional Surveyor</p><p> 7016 Certificate Number</p></div>
---	--

**AMOCO PRODUCTION COMPANY
AMOCO PRODUCTION COMPANY
DRILLING AND COMPLETION PROGRAM**

Prospect Name: Fletcher
Lease: FLETCHER
County: San Juan
State: New Mexico
Date: July 27, 2001

Well No: 1M
Surface Location: 33-31N-8W, 2310 FNL, 1540 FWL
Field: Blanco Mesaverde/Basin Dakota

OBJECTIVE: Drill 450' below the base of the Greenhorn Limestone, set 41/2" production casing, Stimulate LS, CH, MF, PL and DK intervals

METHOD OF DRILLING		APPROXIMATE DEPTHS OF GEOLOGICAL MARKER			
TYPE OF TOOLS	DEPTH OF DRILLING	Estimated GL: 6447		Estimated KB: 6461	
Rotary	0 - TD	MARKER		SUBSEA	MEAS. DEPTH
LOG PROGRAM		Ojo Alamo		4387.1	2074
TYPE	DEPTH INTERVAL	Fruitland Coal	*	3691.3	2563
<u>OPEN HOLE</u>		Pictured Cliffs	*	3189.1	3272
GR-Induction	TD to 7" shoe	Lewis Shale	#	2861	3600
Density/Neutron	TD to 7" shoe	Cliff House	#	1440.2	5021
<u>CASED HOLE</u>		Menefee Shale	#	1239.1	5222
GR-CCL-TDT	TDT - TD to 7" shoe	Point Lookout	#	926.6	5534
CBL	Identify 4 1/2" cement top	Mancos		546.4	5915
REMARKS: - Please report any flares (magnitude & duration).		Greenhorn		-1102.5	7564
		Bentonite Marker		-1149.4	7610
		Two Wells	#	-1221.3	7682
		Dakota MB	#	-1308.8	7770
		Burro Canyon	*	-1506.2	7967
		Morrison	*	-1556.2	8017
		TOTAL DEPTH		-1599	8060
		# Probable completion interval		* Possible Pay	
		DRILL CUTTING SAMPLES		DRILLING TIME	
		FREQUENCY	DEPTH	FREQUENCY	DEPTH
SPECIAL TESTS		10 feet	Production hole	Geograph	0-TD
TYPE					
None					
REMARKS:					

MUD PROGRAM:					
Approx. Interval	Type Mud	Weight, #/ga	Vis, sec/qt	W/L cc's/30 min	Other Specification
0 - 200	Spud	8.6-9.2			
200 - 3700 (1)	Water/LSND	8.6-9.2		<6	
3700 - 7967	Gas/Air/N2/Mist	Volume sufficient to maintain a stable and clean wellbore			
7967 - 8060 (2)	LSND	9.0-9.2		<6	

REMARKS:

- (1) The hole will require sweeps to keep unloaded while fresh water drilling. Let hole conditions dictate frequency.
(2) Mud up 50' above Morrison +/-.

CASING PROGRAM: (Normally, tubular goods allocation letter specifies casing sizes to be used. Hole sizes will be governed by Contract)

Casing String	Estimated Depth	Casing Size	Grade	Weight	Hole Size	Landing Pt, Cmt, Etc.
Surface/Conductor	200	9 5/8"	H-40 ST&C	32#	12.25"	1
Intermediate 1	3700	7"	J/K-55 ST&C	20#	8.75"	1,2
Production	8060	4 1/2"	J-55	11.6#	6.25"	3

REMARKS:

- (1) Circulate Cement to Surface
(2) Set casing 100' into Lewis Shale
(3) Bring cement 100' above 7" shoe

CORING PROGRAM:

None

COMPLETION PROGRAM:

Rigless, 4-6 Stage Limited Entry Hydraulic Frac

GENERAL REMARKS:

Notify BLM/NMOCD 24 hours prior to Spud, BOP testing, and Casing and Cementing.

Form 46 Reviewed by: _____ Logging program reviewed by: N/A

PREPARED BY:	APPROVED:	DATE:	
		21 June 2001	

Cementing Program

Well Name: Fletcher 1M Location: 33-31N-8W, 2310 FSL, 1540 FEL County: San Juan State: New Mexico	Field: Blanco Mesaverde / Basin Dakota API No. Well Flac Formation: Dakota MesaVerde KB Elev (est) 6461 GL Elev. (est) 6447
--	--

Casing Program:

Casing String	Est. Depth (ft.)	Hole Size (in.)	Casing Size (in.)	Thread	TOC (ft.)	Stage Tool Or TOL (ft.)	Cmt Cir. Out (bbl.)
Surface	200	12.25	9.625	ST&C	Surface	NA	
Intermediate	3700	8.75	7	LT&C	Surface	NA	
Production -	8060	6.25	4.5	?	3600	NA	

Casing Properties:

(No Safety Factor Included)

Casing String	Size (in.)	Weight (lb/ft)	Grade	Burst (psi.)	Collapse (psi.)	Joint St. (1000 lbs.)	Capacity (bbl/ft.)	Drift (in.)
Surface	9.625	32	H-40	3370	1400	254	0.0787	8.845
Intermediate	7	20	K-55	3740	2270	234	0.0405	6.456
Production -	4.5	11.6	J-55	5350	4960	154	0.0155	3.875

Mud Program

Apx. Interval (ft.)	Mud Type	Mud Weight	Recommended Mud Properties Prio Cementing:
			PV <20
			YP <10
			Fluid Loss <15
0 - SCP	Water/Spud	8.6-9.2	
SCP - ICP	Water/LSND	8.6-9.2	
ICP - ICP2	Gas/Air Mist	NA	
ICP2 - TD	LSND	8.6 - 9.2	

Cementing Program:

	Surface	Intermediate	Production
Excess %, Bit	100%	80	10
Excess %, Caliper	NA	NA	30
BHST (est deg. F)	60	120	160
Pipe Movement	NA	Rotate/Reciprocate	Rotate/Reciprocate
Rate, Max (bpm)	7	4	2
Rate Recommended (bpm)	6	4	2
Pressure, Max (psi)	200	2000	2000
Shoe Joint	40	80	40
Batch Mix	NA	NA	NA
Circulating prior cmtng (hr)	0.5	1.5	2
Time Between Stages, (hr)	NA	NA	NA
Special Instructions	1,6,7	1,6,8	2,4,6

1. Do not wash pumps and lines.
2. Wash pumps and lines.
3. Reverse out
4. Run Blend Test on Cement
5. Record Rate, Pressure, and Density on 3.5" disk
6. Confirm densitometer with pressurized mud scales
7. 1" cement to surface if cement is not circulated.
8. If cement is not circulated to surface, run temp. survey 10-12 hr. after landing plug.

Notes:

- *Do not wash up on top of plug. Wash lines before displacing production cement job to minimize drillout.
 *** Run TMD cased hole logs to identify pay; Perforating and CH logs can be run rigless.

Surface:

Preflush	20 bbl.	FreshWater
----------	---------	------------

Cementing Program

Slurry 1 TOC@Surface	108 sx Class G Cement + 2% CaCl ₂ (accelerator) 0.25 #/sk Cellophane Flake (lost circulation additive) 0.1% D46 antifoam	125 cuft 0.3132 cuft/ft OH 100 % excess
-------------------------	--	---

Slurry Properties:	Density (lb/gal)	Yield (ft ³ /sk)	Water (gal/sk)
Slurry 1	15.8	1.16	4.95

Casing Equipment:

- 9-5/8", 8R, ST&C
- 1 Guide Shoe
- 1 Top Wooden Plug
- 1 Autofill insert float valve
- 4 Centralizers
- 1 Stop Ring
- 1 Thread Lock Compound

Intermediate:

Fresh Water	20 bbl	fresh water
-------------	--------	-------------

Lead Slurry 1 TOC@Surface	292 sx Class "G" Cement + 3% D79 extender + 2% S1 Calcium Chloride +1/4 #/sk. Cellophane Flake + 0.1% D46 antifoam'	847 cuft
---------------------------------	---	----------

Tail Slurry 2 500 ft fill	107 sx 50/50 Class "G"/Poz + 2% gel (extender) 0.1% D46 antifoam +1/4 #/sk. Cellophane Flake + 2% CaCl ₂ (accelerator)	135 cuft 0.1503 cuft/ft OH 0.1746 cuft/ft csg ann 80 % excess
-------------------------------------	---	--

Slurry Properties:	Density (lb/gal)	Yield (ft ³ /sk)	Water (gal/sk)
Slurry 1	11.4	2.9	17.77
Slurry 2	13.5	1.27	5.72

Casing Equipment:

7", 8R, ST&C

- 1 Float Shoe (autofill with minimal LCM in mud)
- 1 Float Collar (autofill with minimal LCM in mud)
- 1 Stop Ring
- 10 Centralizers (one in middle of first joint, then every third collar)
- 2 Fluidmaster vane centralizers @ base of Ojo
- 7 Centralizers one every 4th joint from Ojo to base of surface casing
- 1 Top Rubber Plug
- 1 Thread Lock Compound

Production:

Fresh Water	10 bbl	CW100
-------------	--------	-------

Lead Slurry 1 TOC@Surface	143 LiteCrete D961 / D124 / D154 + 0.03 gps D47 antifoam + 0.5% D112 fluid loss	306 cuft
---------------------------------	---	----------

Cementing Program

+ 0.11% D65 TIC

Tail
Slurry 2

1645 ft fill

129 sx 50/50 Class "G"/Poz
+ 5% D20 gel (extender)
+ 0.1% D46 antifoam
+ 1/4 #/sk. Cellophane Flake
+ 0.25% D167 Fluid Loss

186 cuft
+ 5 #/sk D24 gilsonite
+ 0.15% D65 TIC
+ 0.1% D800 retarder

Slurry Properties:

Density
(lb/gal)

Yield
(ft³/sk)

Water
(gal/sk)

0.1026 cuft/ft OH

10 % excess

0.1169 cuft/ft csg ann

Slurry 1

9.5

2.14

6.38

Slurry 2

13

1.44

6.5

Top of Mancos

5915

Casing Equipment:

4-1/2", 8R, ST&C

1 Float Shoe (autofill with minimal LCM in mud)

1 Float Collar (autofill with minimal LCM in mud)

1 Stop Ring


39 Centralizers (every third joint)

1 Top Rubber Plug

1 Thread Lock Compound

Note:

1. The job should be pumped at 2-3 bpm max rate. Do not exceed 3 bpm on displacement
2. Wash pump and lines before displacement. Slow to 1 bpm for the last 30 bbl of displacement.



Purposed Pipeline
+/- 1400' FT

**AMOCO
PRODUCTION COMPANY**

Fletcher # 1M
NW¼ Section 33,
T31N, R8W, N.M.P.M.

1100' New BLM Road Construction
T31N, R8W, Sec.33
SW¼NW¼ - 600'
SE¼NW¼ - 500'

APD MAP # 1