

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1135'FSL, 1585'FEL, Sec.27, T-30-N, R-11-W, NMPM

5. Lease Number

NMNM02758

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Murphy D #1R

9. API Well No.

30-045-30849

10. Field and Pool

Aztec Pictured Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☒ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

It is intended to plug and abandon the subject well according to the attached procedure and wellbore diagram.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 3/12/02
TLW

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date 3/19/02

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Murphy D-1R P&A Intent

1. Set CIBP in 2-7/8" casing at 328' (parted casing at 331').
2. Dump bail Class B cement in 2-7/8" casing to 160'.
3. Perforate 2-7/8" casing at 1 shot at 143'.
4. Establish circulation to surface by pumping 1 bbl water.
5. Pump 6 bbls Class B cement. Shut down once cement is circulated to surface, leaving 2-7/8" casing and annulus loaded with cement.
6. Install P & A marker.

Murphy D-1R

Aztec PC

1135' S, 1585' E O - 27 - 30N - 11W

LAT: 36 DEG 46.70'

LONG: 107 DEG 58.50'

GL = 5,955'

KB= 5,967'

Current Wellbore

Surface Casing:

7" 20.0#
Cement: 80 sx
Set @ 139'

J-55
TOC @ circ to surf

Ojo Alamo	@	n/a
Kirtland	@	n/a
Fruitland Coal	@	n/a
Pictured Cliffs	@	n/a

139

TOC 146' CBL

Casing Backed Off at 331'

Production Casing:

2-7/8" 6.5#
Cement: 435 sx
Set @ 2,587'

J-55
TOC @ 146' CBL

TD: 2,587'
PBD: 0,331'

Murphy D-1R

Aztec PC

1135' S, 1585' E O - 27 - 30N - 11W

LAT: 36 DEG 46.70'

LONG: 107 DEG 58.50'

GL = 5,955'

KB= 5,967'

Proposed Wellbore

Surface Casing:

7" 20.0# J-55
Cement: 80 sx TOC @ circ to surf
Set @ 139'

Ojo Alamo @ n/a
Kirtland @ n/a
Fruitland Coal @ n/a
Pictured Cliffs @ n/a

139

Sqz perf shot @ 143'

CIBP set @ 328'

Casing Backed Off at 331'

Production Casing:

2-7/8" 6.5# J-55
Cement: 435 sx TOC @ 146' CBL
Set @ 2,587'

TD: 2,587'
PBSD: 0,331'