5 BLM 1 File

Form 3160-5 (June 1990)

UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31,1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. ION FOR PERMIT -" for such proposals

5. Lease Designation and Serial No. NM-71716 6. If Indian, Allotted or Tribe Name

Use "APPLICATION FOR PERI	MIT - for such pr	Upusais		
SUBMIT IN TRIP	LICATE	T18 19 20 27		
		10.1	<u>,</u>	7. If Unit or CA, Agreement Designation
ge of Well Gas		3	4	
Well X Well	Other (C)	OCT 50/15	4-	a walkana and Na
me of Operator		V.		8. Well Name and No.
gan Production Corp.				Lisbon #2
dress and Telephone No.	V.			9. API Well No.
D. Box 420 , Farmington, NM 87499 (505)	325 - 1821 🚫 🔿	·	<i>)</i>	30 045 30924
tion of Well (Footage, Sec., T., R., M., or Survey Description)				10. Field and Pool, or Exploratory Area
10' Lelet'		and marks and		Harper Hill FR Sand PC
50° FNL & 1005° FWL (SW/4 NW/4)				11. County or Parish, State
it E, Sec. 11, T30N, R14W, NMPM				San Juan, NM
	ENATURE OF	NOTICE DEPORT	OR O	THER DATA
. CHECK APPROPRIATE BOX(s) TO INDICATE	E NATURE OF	TYPE OF ACT	TION	
TYPE OF SUBMISSION	Abandonment	TIFE OF AUT	X X	Change of Plans
Notice of Intent				New Construction
Subsequent Report				Non-Routine Fracturing
Subsequent Report				Water Shut-Off
l =				Conversion to Injection
	Other			Dispose Water
Final Abandonment Notice	l Caioi		_	(Note: Report results of multiple completion on Well
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02.		s, including estimated date of sta inent to this work.)*	arting any pro	Completion or Recompletion Report and Log form.) posed work. If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all perfinent details give subsurface locations and measured and true vertical depths for all	185'. 3% CaCl ₂ (153	cu. ft.)	arting any pro	Completion or Recompletion Report and Log form.) posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface.	185'. 3% CaCl ₂ (153	cu. ft.)	arting any pro	posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface.	185'. 3% CaCl ₂ (153	cu. ft.)	arting any pro	posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface. Pressure tested casing and blow out p	185'. 3% CaCl ₂ (153 preventer to 600	cu. ft.)	Date	posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all perlinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface. Pressure tested casing and blow out p	185'. 3% CaCl ₂ (153 preventer to 600	cu. ft.) psi, held ok.		posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface. Pressure tested casing and blow out p	185'. 3% CaCl ₂ (153) breventer to 600	cu. ft.) psi, held ok.		posed work If well is directionally drilled,
Describe Proposed or Completed Operations (Clearly state all pertinent details give subsurface locations and measured and true vertical depths for all Spud 12-1/4" hole on 10/07/02. Set 8-5/8" 23 lb./ft. casing. Landed @ Cemented with 130 sx. Class "B" with Circulated 4 bbls. cement to surface. Pressure tested casing and blow out p	185'. 3% CaCl ₂ (153) breventer to 600	cu. ft.) psi, held ok.	Date	posed work If well is directionally drilled,