

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO. 30-045-31023
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. SF-078988
7. Lease Name or Unit Agreement Name:  NORTHEAST BLANCO UNIT
8. Well No. 323
Pool name or Wildcat: Basin -Dakota

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other:
2. Name of Operator: Devon Energy Production Co. L.P.
Address of Operator: Attn: Diane Busch 20 N. Broadway Okla. City, OK 73102

3. Well Location  Unit Letter F: 1777 feet from the North line and 1375 feet from the West line.  Section: 19 Township 31N Range 6W NMPM County San Juan 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6397' GL
--

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: Change downhole co-mingle process <input checked="" type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

It is our request to change the downhole comingle testing/allocation method to the attached procedure.

DHC 929AZ

I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE	<u>Diane Busch</u>	TITLE <u>Sr. Operations Technician</u> DATE <u>10/31/02</u>
Type or print name	<u>Diane Busch</u>	Telephone No. <u>(405) 228-4362</u>
(This space for State use)		
APPROVED BY	<u>STEVEN N. HAYDEN</u>	TITLE <u>SENIOR OIL &amp; GAS INSPECTOR</u> DATE <u>11/1/02</u>
Conditions of approval, if any:		

## Method of Allocation

Devon Energy recommends the following procedure to allocate downhole commingled production between the Basin-Dakota and the Blanco-Mesaverde pools within the Northeast Blanco Unit:

- The Mesaverde and Basin-Dakota formations will be completed simultaneously.
- A single 2-3/8" tubing string will be run in the well, with a packer isolating the two horizons.
- The Dakota completion will be produced up the tubing string.
- The Mesaverde completion will be produced up the 2-3/8" x 4-1/2" annulus.
- Production from each zone will be measured separately using a 3 phase metering device prior to flowing through a mutual production separator. Total well stream gas will be measured using a conventional orifice plate meter tube located downstream of the production separator.
- The completions will be flow tested separately for 90 days to establish a stabilized rate and trend.
- Following the testing period the packer will be removed and the two pools will be downhole commingled. Total well production will flow through common surface facilities and total produced gas will be measured using a conventional orifice plate meter tube.
- Production will be allocated between the Mesa Verde and Dakota intervals by applying the variable percentage schedule to the daily total well production.

The Variable Percentage Schedule was derived using Mesa Verde and Dakota production type curves. These type curves were generated by normalizing production data from surrounding wells. The variable percentage schedule is required due to the dissimilar decline trends exhibited by the Mesa Verde and Dakota. Figure 1 depicts a typical Mesa Verde – Dakota production allocation. The actual percentages will vary from well to well, depending on well productivity.




Figure 1

The Basin-Dakota type curve was generated from normalized production of 40 offsetting Basin-Dakota producers. The Basin-Dakota type curve clearly defines the decline rate for the life of a well. Comparison of this type curve with the production schedule obtained by using flow test data demonstrates the reliability of this method for projecting production. (See Figure 2) The curve covers a three and one half year period with a variance in cumulative normalized production of only 165 MCF.





Figure 2

The Blanco – Mesa Verde type curve was generated from normalized production of 12 offsetting Blanco-Mesa Verde producers. Comparison of this type curve with the production schedule obtained by using flow test data demonstrates the reliability of this method for projecting production. (See Figure 3) The curve covers a four year period with a variance in cumulative normalized production of only 3,382 MCF.

**Mesa Verde Type Curve**



**Figure 3**