Orm 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No. NMSF080597

6	If Indian	Allottee	or Tribe	Name

	<u> </u>							
SUBMIT IN TRI	PLICATE - Other instruc	ctions on rever	se side.		7. If Unit or CA/Agree	ment, Name and/or No.		
1. Type of Well ☐ Oil Well ☑ Gas Well ☐ Other				63" 2	8 Well Name and No. GARTNER A 1B			
2. Name of Operator BP AMERICA PRODUCTION CO Contact: MARY C E-Mail: co				* *	-9. API Well No.			
3a. Address P. O. BOX 3092 HOUSTON, TX 77253 3b. Phone No Ph: 281.366					10. Field and Pool, or Exploratory BASIN DAKOTA BLANCO MESAVERDE			
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Descriptio	T- 24		11. County or Parish, a	and State			
Sec 28 T30N R8W SWNW Lot E 1450FNL 1020FWL SAN JUAN COUNTY, NM 36.47100 N Lat, 107.41300 W Lon								
12. CHECK APP	ROPRIATE BOX(ES) T	O INDICATE N	ATURE OF N	IOTICE, RI	EPORT, OR OTHER	RDATA		
TYPE OF SUBMISSION	YPE OF SUBMISSION TYPE OF ACTION							
	☐ Acidize	□ Deepe	n	☐ Product	tion (Start/Resume)	■ Water Shut-Off		
☐ Notice of Intent	☐ Alter Casing	□ Fractu	re Treat	☐ Reclam	ation	■ Well Integrity		
■ Subsequent Report	☐ Casing Repair	□ New (Construction	☐ Recomp	olete	Other		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug a	nd Abandon	☐ Tempor	rarily Abandon	Well Spud		
	☐ Convert to Injection	☐ Plug F	Back	☐ Water I	Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) APD ROW APD ROW Well Directionally Drilled. MIRU Drilling Unit. @ 12.00 Hrs on 06/07/2002 Spud a 13 1/2" surface hole. Drilled to 146'. RU & ran 9 5/8", 32.3# H-40 surface CSG to 140'. CMT w/150 SXS CLS G + 3% S-1, 0.25#/SX D19, 15.8 PPG, Yield 1.16 cuft/sx. Circ 10 BBLS good CMT to pit. NU BOP & tested to 750# high, 250# low. Test OK Drilled out CMT. Drilled a 8 3/4" hole to 2699'. RU & set 7", 20# & 23#, J-55 CSG to 2816'. CMT w/250 SXS CLS G Lead mixed @ 11.7 PPG, yield 2.61 cuft/sx and 65 SXS 50/50 POZ mixed @13.5 PPG, yeild 1.26 cuft/sx Tail. Circ 17 BBLS CMT to pit. Pressure test to 1500#. Test OK.								
14. I hereby certify that the foregoing is true and correct. Electronic Submission #12155 verified by the BLM Well Information System For BP AMERICA PRODUCTION CO, sent to the Farmington Committed to AFMSS for processing by Adrienne Garcia on 06/25/2002 (02AXG0252SE)								
Name (Printed/Typed) MARY C	ORLEY		Title AUTHO	RIZED REI	PRESENTATIVE			
Signature (Electronic	Submission)		Date 06/19/2	002				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved By ACC	CEPTED			ENNE GAF ROLEUM EI		06/25/2002		
Conditions of approval, if any, are attact certify that the applicant holds legal or e which would entitle the applicant to con	quitable title to those rights in t	bes not warrant or the subject lease	Office Farm	ington				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #12155 that would not fit on the form

32. Additional remarks, continued

Drill out CMT. Drilled a 6 1/4" hole to 5811'. TD @ 16.45 hrs on 06/14/2002. RU & set 4 1/2", 11.6#, J-55, production liner to 5809'. CMT w/225 SXS of 9.5 PPG Litecrete CMT, 2.52 cuft/sx. 30 BBLS good CMT to pit. TOL @ 2682'. TOC 2682'.

RDMOSU Rig release @ 24.00 hrs 06/15/2002.