For	A PROVED
	JUN 2 2 1956
	JERRY W. LONG

(SUBMIT IN TRIPLICATE)

UNITED STATES

Approvate aprice -
Land Office Sunta Fe 078195
Sellers Unit

SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUBSQUENT REPORT OF WATER SHIT-OFF. SUBSQUENT REPORT OF SHOTTING OR GLIDIZE. SUBSQUENT REPORT OF SHOTTING OR GLIDIZE. SUBSQUENT REPORT OF SHOTTING OR GLIDIZE. SUBSQUENT REPORT OF SHOTTING CASING. SUBSQUENT REPORT OF SHOTTING CASING. SUBSQUENT REPORT OF ALTERING CASING. SUBSQUENT REPORT OF ALT	JUN 2 1950	UNITED STATES
SUNDRY NOTICES AND REPORTS ON WELLS SUBSQUENT REPORT OF WATER SHUT-OFF. SUBSQUENT REPORT OF SHOTHOR OR ACIDIZING. SUBSQUENT REPORT OF ALTERING CASING. SUPPLEMENTARY WELL MISTORY. SUBSQUENT REPORT OF ALTERING CASING. SUPPLEMENTARY WELL MISTORY. SUBSCQUENT REPORT OF ALTERING CASING. SUBSCQUENT REPORT O	LONG DEDAK	PTMENT OF THE INTERIOR
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUBSCOUNT REPORT OF WATER SHUT-OFF. SUBSCOUNT REPORT OF WATER SHUT-OFF. SUBSCOUNT REPORT OF SHOOTING OR ACIDIZING. SUBSCOUNT REPORT OF ALTERING CASING. OTICE OF INTENTION TO SHUT OR ALTER CASING. OTICE OF INTENTION TO PALL OR REPAIR WELL. SUBSCOUNT REPORT OF ALATERING CASING. OTICE OF INTENTION TO ABANDON WELL. (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPA) (INDICATE ASSOVE BY CHECK MARK NATURE OF SUBSCOUNTS OF ALL PROPORTION OF ALL PROPORTI	CTING DISTRICT ENGINEE	GEOLOGICAL SURVEY
SUBSCULENT REPORT OF WATER SHUT-OFF. SUBSCULENT REPORT OF SHOOTING OR ACTIONING OTHER OF INTENTION TO GENELLOR REPARK WELL OTHER OF INTENTION TO TEST WATER SHUT-OFF. SUBSCULENT REPORT OF ALTREING CASING. SUBSCULENT REPORT OF RE-DRILLING OFF. SUBSCU		GEOLOGIO:
SUBSCULENT REPORT OF WATER SHUT-OFF. SUBSCULENT REPORT OF SHOOTING OR ACTIONING OTHER OF INTENTION TO GENELLOR REPARK WELL OTHER OF INTENTION TO TEST WATER SHUT-OFF. SUBSCULENT REPORT OF ALTREING CASING. SUBSCULENT REPORT OF RE-DRILLING OFF. SUBSCU		
SUBSQUENT REPORT OF WITER SHUT-OFF. SUBSQUENT REPORT OF ALTERING CASING. STICE OF INTENTION TO TEST WATER SHUT-OFF. SUBSQUENT REPORT OF ALTERING CASING. SUBSQUENT REPORT OF REDBILLING OF REPORT. OTTICE OF INTENTION TO PULL OR ALTER CASING. SUBSQUENT REPORT OF REDBILLING OF REPORT. OTTICE OF INTENTION TO PULL OR ALTER CASING. SUPPLEMENTARY WELL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK WILL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK MILL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE BANK NATURE OF REPORT OF REDBILLING. (INDIC		DEPORTS ON WELLS
SUBSQUENT REPORT OF WITER SHUT-OFF. SUBSQUENT REPORT OF ALTERING CASING. STICE OF INTENTION TO TEST WATER SHUT-OFF. SUBSQUENT REPORT OF ALTERING CASING. SUBSQUENT REPORT OF REDBILLING OF REPORT. OTTICE OF INTENTION TO PULL OR ALTER CASING. SUBSQUENT REPORT OF REDBILLING OF REPORT. OTTICE OF INTENTION TO PULL OR ALTER CASING. SUPPLEMENTARY WELL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPACHING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK WILL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK MILL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REDBILLING. (INDICATE BANK NATURE OF REPORT OF REDBILLING. (INDIC	CHINDRY NOTIC	CES AND REPORTS ON WELL
For intention to original prince of intention to original prince of intention to themse plans. Subsequent report of shorting or allours subsequent report of respective of intention to rest water shut-off. Subsequent report of allours subsequent report of allours of respective of intention to rest water shut-off. Subsequent report of respective of respective subsequent report of report, notice of report of respective subsequent report of report of respective subsequent report of report of report of report, notice of report of repo	SOMDICE INC.	X CHIT OFF
Subsequent report of Altering Casing. Force of Intention to test water sour-off. Subsequent report of Altering Casing. Subsequent report of Altering Casing. Subsequent report of Altering Casing. Subsequent report of Abandoning Supplementary Well History. Supplementary Well History. Subsequent report of Abandoning Supplementary Well History. Supp	DDU	SUBSEQUENT REPORT OF WATER SHOT-OF
Subsequent Report of Re-Drilling of Report of Re-Drilling of Intention to Shoot or Acidize. OTICE OF INTENTION TO DULL OR ALTER CASING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAYS). (INDICATE ABOVE BY CHECK	TICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING CASING
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION, 1956. Section 30 30N 10W BEEN (Neridian) (Neridian) (State or Territory) (State or Territory) The elevation of the derrick floor above sea level is 6059 ft. DETAILS OF WORK (State names of and expected depths to objective annds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Bepth 5043'. Ban 23 joints 5 1/2", 15.50%, J-55 casing (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at 423'. casented with 62 1/2 sacks regular cement, 62 1/2 sacks Possix, 31 1/4f 4323', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Possix, 31 1/4f 4323', cemented with 62 1/2 sacks regular example. The standard of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 ps1, 10 minutes. Squeezed top of liner with 100 sacks regular example. (90; sacks into formation). Final standing pressure 2000 ps1 for 15 minutes. 1 understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	OTICE OF INTENTION TO CHANGE TELESCOPE	SUBSEQUENT REPORT OF RE-DRILLING G TEPAN
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION, 1956. Section 30 30N 10W BEEN (Neridian) (Neridian) (State of Territory) (State of Territo	OTICE OF INTENTION TO RE-DRILL OR REPAIR V	VELL SUBSEQUENT REPORT OF ARANDONMENT
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION, 1956. Section 30 30N 10W BEEN (Need and Sec. No.) (Real Juan (State of Territory) (State of Territory) The elevation of the derrick floor above sea level is 6059 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Bepth 5043°. Ran 23 joints 5 1/2°, 15.50%, J-55 casing (as a limer) 719°, set at 5042° with Burns liner hanger. Top of liner at 4233°, cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/45 4323°, cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/45 4323°, cemented with 62 1/2 sacks regular essent; 323°. May 11, 1956. Set Baker retrievable retainer at 4255°. Tested top of liner, would not hold pressure. Tested 7 5/8° casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular essent (90; sacks into formation). Final standing pressure 2000 psi for 15 minutes.	OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF THE SUBSECUENT REPORT OF
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAPPARATION, 1956. Section 30 30N 10W BEEN (Neridian) (Neridian) (State of Territory) (State of Territo	OTICE OF INTENTION TO PULL OR ALTER CASIN	G. SUPPLEMENTANT
Well No. 3-A is located 90 ft. from S line and 90 ft. from W line of sec. 30 Section 30 30N 10W MPM (Kange) (Meridian) (Meridian) (Meridian) (Meridian) (Meridian) (State or Territory) The elevation of the derrick floor above sea level is 6059 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) May 10, 1956. Total Depth 5043'. Ban 23 joints 5 1/2', 15.50%, J-55 casing (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 14233', comented with 62 1/2 sacks regular coment, 62 1/2 sacks Posmix, 31 1/4% (as a liner)	OTICE OF INTENTION TO ABANDON WELL	11.5. martin
Well No. 3-A is located 990 ft. from S line and 890 ft. from W line of sec. 30 Section 30 (Kese, and Sec. No.) (Kese, and Sec. No.) (Kese, and Sec. No.) (County or Subdivision) (County or Subdivision) (State or Territory) (State or Te	Office of investment of the second	NATIBE OF REPORT, NOTICE, OR OTHER DATA
Well No. 3-A is located 990 ft. from S line and 890 ft. from W line of sec. 30 Section 30 (Kese, and Sec. No.) (Kese, and Sec. No.) (Kese, and Sec. No.) (County or Subdivision) (County or Subdivision) (State or Territory) (State or Te	(INDICATE ABOVE B)	CHECK MARK NATURE OF THE STATE
Section 30 30N (Geo. and Sec. No.) (Geo. and Sec		May 23, , 1920
Section 30 30N (Geo. and Sec. No.) (Geo. and Sec		
Section 30 (1) (1) (Range) (2) (Meridian) (3) (Meridian) (4) Sec. and Sec. No.) (Field) (County or Subdivision) (State or Territory) (State or Terr		ft from line and 90 ft. from W line of sec.
Section 30 (Kange)	ell No. 3-A is located yo	into the [S]
Response (4 Sec. and Sec. No.) (Yeld) (County or Subdivision) (State or Territory) (State or Territory) (State or Territory) (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Depth 5043'. Ran 23 joints 5 1/2", 15.50%, J-55 casing (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4233', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/4% (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4233'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. Ney 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90: sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	2010	
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) [State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) [May 10, 1956. Total Depth 5043'. Ran 23 joints 5 1/2", 15.50%, J-55 casing (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4233', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/4% [as 2] [as a liner of the same survey at 4323'. [May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. [Squeezed top of liner with 100 sacks regular cement (90; sacks into formation). [Squeezed top of liner with 100 sacks regular cement (90; sacks into formation). [Squeezed top of liner with 100 sacks regular cement (90; sacks into formation). [Squeezed top of liner with 100 sacks regular cement (90; sacks into formation).	E Section Jo	(Range) (Range)
DETAILS OF WORK DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Bepth 5043'. Ran 23 joints 5 1/2", 15.50#, J-55 casing (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4323', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/4# Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90; sacks into formation). Final standing pressure 2000 psi for 15 minutes.		(State or Territory)
DETAILS Of the proposed depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Depth 5043'. Ban 23 joints 5 1/2", 15.50%, J-55 casing (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner survey at 4323'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, Would not hold pressure. Tested 7 5/8" easing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90:sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	(Field)	•
DETAILS Of the proposed depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Depth 5043'. Ban 23 joints 5 1/2", 15.50%, J-55 casing (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner survey at 4323'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, Would not hold pressure. Tested 7 5/8" easing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90:sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		have sea level is 6059 ft.
DETAILS OF Work and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) May 10, 1956. Total Depth 5043'. Ran 23 joints 5 1/2", 15.50%, J-55 casing (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 719', set at 5042' with Burns liner hanger. Top of liner at (as a limer) 729', set at 5042' with Burns liner survey at 4323'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90: sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	The elevation of the derrick floor a	pove sea to the
May 10, 1956. Total Depth 5043'. Ran 23 joints > 1/2, 1750 of liner at (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4323', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/4f Flocele, and 2f Gel. Top of cement by temperature survey at 4323'. Flocele, and 2f Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		DETAILS OF WORK
May 10, 1956. Total Depth 5043'. Ran 23 joints > 1/2, 170 of liner at (as a liner) 719', set at 5042' with Burns liner hanger. Top of liner at 4323', cemented with 62 1/2 sacks regular cement, 62 1/2 sacks Posmix, 31 1/4# Flocele, and 2# Gel. Top of cement by temperature survey at 4323'. Flocele, and 2# Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" easing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	denths to objectiv	e sands; show sizes, weights, and lengths or proposed outside (
(as a liner) [19] 4323', cemented with 62 1/2 sacks regular cement, 62 1/2. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, Would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Yould not hold pressure with 100 sacks regular cement (90 sacks into formation). Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Pago Batural Gas Company	(State names of and expected depths ing	points, and an other services 1/0° 15.50%. J-55 casing
(as a limer) [19] 4323', cemented with 62 1/2 sacks regular cement, 62 1/2. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. Flocele, and 2% Gel. Top of cement by temperature survey at 4323'. May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, Would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Yould not hold pressure with 100 sacks regular cement (90 sacks into formation). Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Pago Entural Gas Company	notel Depth	5043'. Ran 23 Joints 7 1/2 Top of liner at
Flocele, and 2% Gel. Top of cement by temperature survey. Hey 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. would not hold pressure with 100 sacks regular cement (90 sacks into formation). Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Matural Gas Company	May 10, 1970. 10 set at	5042' with Burns liner mangalia sacks Posmix, 31 1/4#
May 11, 1956. Set Baker retrievable retainer at 4255'. Tested top of liner, would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	(as a limer) (1)	2 sacks regular committy ourvey at 4323'.
May 11, 1956. Set Baker retrievable retainer at the second pai, 10 minutes. Would not hold pressure. Tested 7 5/8" casing, held 1200 psi, 10 minutes. Squeezed top of liner with 100 sacks regular cement (90 sacks into formation). Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	4323', Cementos Gel. Top	of cement by temperature
Squeezed top of liner with 100 sacks regular control of liner with 100 sacks regular control of liner with 100 sacks regular control of liner	krocere, ere al	t koss! Tested top of liner,
Squeezed top of liner with 100 sacks regular contents. Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Estural Gas Company	May 11, 1956, Set Baker 1	retrievable retained held 1200 psi, 10 minutes.
Final standing pressure 2000 psi for 15 minutes. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company Fi Pago Estural Gas Company	would not hold pressure.	Tested 77/0 color generat (90:sacks into formation).
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	Sincered top of liner with	100 sacas requirements.
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	Final standing pressure 2	000 ber rer =>
Company El Pago Batural Gas Company		
Company El Pago Batural Gas Company		
Company El Pago Batural Gas Company		Survey before operations may be commenced.
Company El Pago Batural Gas Company	tales this plan of work must	receive approval in writing by the Geological Survey
Address Box 997 Fermington, N.M. Title Petroleum Engineer	I understand that this plan of a some	
Address Box 997 By Surface Regimeer Title Petroleum Engineer	Company El Paso Batural	as Company
Address Box 997 By By Title Petroleum Engineer		
Fermington, N.M. Title Petroleum Engineer	Address Box 997	- VIIIan
Title Petroleum Engineer		Ву
Title	Farmington, N.M.	Betroleum Begineer
		Title FEW VI
		U. S. GOVERNMENT PRINTING OFFICE 16-8437-6