

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Mobil Oil Corporation
3. ADDRESS OF OPERATOR  
9 Greenway Plaza, Suite 2700, Houston, TX 77046
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 790' FWL + 855' FSL, Sec. 20,  
AT TOP PROD. INTERVAL: T-30-N, R-12-W.  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☒ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON\* ☐ ☐

(other) ☐ ☐

5. LEASE  
NM 024158
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Rice
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Basin Dakota
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 20, T-30-N, R-12-W
12. COUNTY OR PARISH  
San Juan
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5674 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well currently T.A. w/mud on formation. Propose to:

- 1) Pull 2-3/8" tubing and Packer.
- 2) Run mill to PBTD and circulate clean.
- 3) Set Retr. Bridge Plug below 4500'. Squeeze hole in casing w/ 150 sxs.
- 4) Drill out cement Plug and swab dry to test for leak. (Hole indicated to be between 3200' - 4100').
- 5) Run completion string; spot 500 gals. 15% MCA across Basin Dakota Perfs 6316 - 6445. Pump into formation.
- 6) Set Packer at ~6280' & swab well.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Virginia Sheward TITLE Authorized Agent DATE July 13, 1978

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

