

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee

Lease No. 1-149-1NB-7653

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 16, 1961

Well No. Navajo A-#2 is located 1650 ft. from N line and 330 ft. from E line of sec. 4  
NE 1/4 Sec. 4 30N 17W NMPH  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Undesignated San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5132 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Set 41 ft. 10 3/4 casing cemented with 15 sacks  
Drilled 8 1/2 hole to 610 ft. dry hole  
Drilled 6 1/2 hole to 1135 ft. Ran 4 1/2 casing to T.D. Cemented with 60 sacks. Top of Dakota 1090 ft.  
Perforated from 1093' to 1096'.  
Froed with 5,000 gals. oil. Recovered 3,000 gals.  
Plan to  
Squeeze off perforations with Halliburton Pump truck. Leave 100 ft. cement above perforations.  
Cement plug 610' to 510'  
Cement plug 100 ft. to surface  
Erect dry hole marker and sign.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company King Oil Company  
Address 735 Petroleum Club Bldg.  
Denver 2, Colorado

By Bernard King  
Title President