1-File

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELL	L
---	---

Revised 12-1-55

200]	BL	nco		Fc	rmation	<u> </u>	less Verd	e	County_	San J	uan	
											10-16-57	
mţ	any Pa	cific l	Northwe	st Pir	eline I	Lease	an Juan	32-7	We]	ll No	18-5	
it	<u>I</u> 5	Sec	5 Twp	31.N	Rge		Purc	haser	Not Conne	ected		
.si	7 ", ng_5" w	/t	I.	D	Set	at_610	% ' Pe:	rf	55 7 4'	To_	6070'	
	ng 1-1/4 %											
	Pay: From_											
	ucing Thru:										-	
	of Complet						Sind	rla_Brade	nhoad_C	C 0m (G.O. Dual	
							ED DATA	-	•			
st	ed Through	(Prov	<u>er) (Ö</u>	loke)	(Meter)		n 10 day	s	Type Tap	os		
_		F	low Dat				Tubing		Casing D)ata	T	
	(Prover) (Prover)	(Cho (Orif	ke) ice)	Press.	Diff.	•	Press.				Duration of Flow	
ļ.	35560x			psig	h _w	°F.	psig	°F.	psig		Hr.	
T	3/4"			175		620	450 325		1188 175		2 1	
†				112		_ 02	<u> </u>		+17	UZ.	3 hours	
I										 		
Ŧ												
	Coefficient (24-Hour)					Factor		Factor	Compress. Factor Fpv 1.017		Q-MCFPD	
I												
╀												
L									 			
	iquid Hydrod y of Liquid		ocarbon	s		SSURE CA	ALCU ATIO	Speci Speci	fic Gravi		rator Gas ing Fluid 1440.0	
			(1-	e -s)	-			Pc	1200	_Pc	1440.0	
	P _w Pt (psia)	Pt ²	F _c Q		(F _c Q) ²	(F ₀	Q) ² -e ^{-s})	337 P _w 2	P _c -P _w ²	P	1. Pw Pc	
-						-		113.6	1326.4	b	1.09	
						1				 	-i	
L										 		
1	ute Potenti	c Nort	hwest 1	Pipeli:	ne Corpo	MCFPD;		.75/ 1.0	x667			
PA	NY Pacifi		-									
IPA RE	SS 4054 We	st Bro	edvay.	Farmi	ngton. N	ew Mexi	co		· · · · · · · · · · · · · · · · · · ·			
IPA ORE ONT	NY Pacifi SS 4054 We and TITLE SSED	st Bro	edvay.	Farmi	ngton. N	ev Mexi Enginee	co r					
IPA ORE ONT 'NE	SS 4055 We and TITLE	st Bro	edvay.	Farmi	ngton. N	ev Mexi Enginee	co r			- al		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw Differential meter pressure, inches water.
- F_g Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

ALIEC DIS	TRICT OFFICE	SION
No Copies Rece	lved 3	
	PUTTON	
to the second	To CHIAED	an death age one of
13 n 4 e	7	
1-5-42 23.3		Notation,
Parties of the Partie		
()		-