

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

VASTAR RESOURCES, INC.

3. Address and Telephone No.

1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SWNW 1850' FNL & 1190' FNL SEC. 34, T-32N, R-5W

FORM APPROVED
Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 30016

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8910195960

8. Well Name and No.

CARRACAS #112

9. API Well No.

30-039-24169

10. Field and Pool, or Exploratory Area

BASIN FRUITLAND COAL

11. County or Parish, State

RIO ARRIBA, N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **RE PERF & RE FRAC**

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Vastar elected to reperforate and refrac the Fruitland Coal in the subject well in an attempt to increase gas flow rates. Reperforated Fruitland Coal fm 3080' to 3087', 3099'-3128' and 3133'-3137', 40' w/ 4 spf adding 160 holes w/ 0.42" diameter and treated all perms w/ 1000 gal 10 % formic acid followed w/ 130,195 gal 25 # Delta frac 140 gel w/ sandwedge containing 2910 sx 20/40 Brady sand. After cleaning out the 5 1/2" csg to 3207', (PBD), a 2 3/8", 4.7#, J-55, 8RD EUE tbg assembly was run w/ an 'X' nipple and WL Re-entry guide. No pkr, EOT at 3061'. Flow and clean well to a flowback tank. Operator will set production equipment and return the well to production. Operations started on 05/19/2000 and were completed on 05/31/2000.

cc: BLM, Durango (Or + 3)

N. Hall
Well File

14. I hereby certify that the foregoing is true and correct

Signed Tom Hagan

Title **WORKOVER SUPERVISOR**

Date **06/04/2000**

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

ACCEPTED FOR RECORD

JUN 13 2000

NMOC

3Y SN FIELD OFFICE

There is a
DAK - w/
different
model.
Garage 5 W 34
Main # 5