

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

GEL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

NASSAU RESOURCES, INC.

3. ADDRESS OF OPERATOR

P O Box 809, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1170' FNL - 1480' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7388' GL; 7397' KB

5. LEASE DESIGNATION AND SERIAL NO.

NM 28277

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Carracas Unit

8. FARM OR LEASE NAME

Carracas Unit 20 B

9. WELL NO.

#3

10. FIELD AND POOL, OR WILDCAT

WC Fruitland

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T32N, R4W, NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud, surface csg. & test

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

MI & RU Four Corners Rig #7.

Spudded 12-1/4" hole at 12:15 pm, 10/27/88.

Ran 8 jts. of 9-5/8", 36#, J-55 csg. (368') set at 380' KB.

Cemented w/ 195 sx of Class "B" w/ 2% CaCl (230 cu.ft.)

Plug down at 10:30 pm, 10/27/88.

Circulated 10 bbls. cement to surface.

W.O.C. 11 hrs.

Pressure tested surface casing to 1000 psi for 30 min.

Held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen
James S. Hazen

TITLE

Field Supt.

DATE 10/31/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side