## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No.

## NM 30584

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRI	IPLICATE AND TO THE STATE OF TH	7. If One of OA, Agreement Designation
. Type of Well Oil Gas		CARRACAS UNIT
☐ Well ☐ Other	55 16 17 18 70	8. Well Name and No.
. Name of Operator	A COLOR	CARRACAS 13 B #7
VASTAR RESOURCES, INC.		9. API Well No.
Address and Telephone No.	JUL 2000 🔀	30-039-24559
1816 E. MOJAVE ST., FARMINGTON, NM 874		10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Description)	O COLOGNION S	BASIN FRUITLAND COAL
	COLOGNIDIV S	11. County or Parish, State
SWNE 1650' FNL & 1800' FEL SEC. 13, T-32N	I, R-4W NAPM	RIO ARRIBA, NM
12. CHECK APPROPRIATE BOX(s) TO INDI	ICATE NATURE OF NOTICE REPORT, OR OTHER D	ATA
TYPE OF SUBMISSION		
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
•	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	OtherRE-PERF & RE-FRAC	Dispose Water
		(Note: Report results of multiple completion on Well
		Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Vastar elected to reperforate and refrac the Fruitland Coal in the subject well in an attempt to increase gas flow rates. Reperforated Fruitland Coal fm 2069'-2090' & 2097'-2100', 24' w/ 4 spf adding 96 holes w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 89,672 gal 25# 20# Delta frac 140 gel w/ sandwedge containing 1980 sx 20/40 Brady sand. After cleaning out the 5 1/2" csg to 2581' (3275' PBTD), a 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL Re-entry guide. No pkr, EOT at 2057'. Flowed and cleaned well to a flowback tank and returned the well to production. Operations started on 06/09/2000 and were completed on 06/27/2000.

cc: BLM, Farmington (Or + 3)			
N <del>. L</del> iall Well Pile			_
14. I hereby certify that the foregoing is true and correct			
Signed Im Mangu	Title WORKOVER SUPERVISOR	Date06/28/2000	_
(This space for Federal or State office use)			=
Approved by	Title	Date	_
Conditions of approval, if any:			

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

