Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPR	OVED
Budget Bureau No	. 1004-0135
Expires: March	31, 1993

Ex	pire	s: Ma	rch	31	1	99	3	
 				-				

6. If Indian, Allottee or Tribe Name

NM 59696

UNDRY NOTICES	AND REPORTS	ON WELLS	

S Do not use this form for proposals to drill or to deepen or reentry to a different leservoir. Use "APPLICATION FOR PERMIT—" for such proposals

7. If Unit or CA, Agreement Designation
 Carracas Unit

(Note: Report results of multiple completion on Well

SUBMIT IN TRIPLICATE	7. If Ollt of CA, Agreement Designation
1. Type of Well Oil	Carracas Unit 8. Well Name and No.
2. Name of Operator	Carracas Unit-PC 27B #8 9. API Well No.
NASSAU RESOURCES, INC. OGRID #015515 3. Address and Telephone No.	30-039-25696
P O BOX 809, Farmington, N.M. 87499	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Carracas Pictured Cliff
	11. County or Parish, State
2460' FNL - 610' FEL	
Sec. 27, T32N, R4W, NMPM	Rio Arriba, N.M.

12.	CHECK APPROPRIATE BO	T, OR OTHER DATA	
	TYPE OF SUBMISSION	TYPE OF ACTION	
	Notice of Intent	Abandonment	Change of Plans
	Subsequent Report	Plugging Back	New Construction Non-Routine Fracturing
	Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection
		CX Other 5-1/2" csg. & cement	Dispose Water

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 4310' on 8/22/97.

Ran 106 jts. 5-1/2", 15.5#, R-55, LTC YB casing. Set at 4305.22' KB with float at 4264.49' KB & DV tool at 2202.88' KB.

Cemented 1st stage: 30 bbl. water flush followed by 246 sx 65/35 pos + 12% gel, 34/sk KCl seal, 1/44/sk cello flake (632.22 cu.ft.) followed by 125 sx 50/50 pos + 1/4#/sk cello flake/sk (173.75 cu.ft.) 805.97 cu.ft. on 1st stage. Circulated 5 bbls. to surface. PLUG DOWN 1ST STAGE 2:30 PM, 8-23-97.

Cemented 2nd stage: 30 bbl. water flush followed by 265 sx 65/35 pos + 12% gel, 3f/sk KCl seal, 1/4f/sk cello flake (681.05 cu.ft.) followed by 25 sx 50/50 pos + 1/4#/sk cello flake/sk (34.75 cu.ft.) cu.ft. on 2nd stage. Circulated 3 bbls. to surface. PLUG DOWN 2ND STAGE 7:00 PH, 8-23-97ERED TOTAL OF 1,521.77 CU.FT. FOR BOTH STAGES.

Full returns throughout job. Set 65,000# on slips.

SEP 1 8 1997

RIG RELEASED AT 10:00 PM, 8-23-97.

		BY
4. I hereby certify that the foregoing is true and correct Signed Mantalum Fran Perrin	Title Regulatory Liaison	Date 9/9/97
(This space for Federal or State office use)		ACCEPTED FOR HELOHD
Approved by	Title	AUCLI Date

SEb 18 188/

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictions or representations as to any matter within its jurisdiction.