

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Taurus Exploration, U.S.A., Inc.

3. Address and Telephone No.

2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1300' FNL, 720' FEL, Section 31, T32N, R5W, N.M.P.M.

5. Lease Designation and Serial No.

SF-080657

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-5 Unit

8. Well Name and No.

San Juan 32-5 Unit 9R

API Well No.

10. Field and Pool, or exploratory Area

Blanco MV

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Int. Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/7/98 Drilled to 4915'. TOH. Pick up core barrel and core from 4915' to 5095' in 3 barrel runs.

10/11/98 Drilled to 5350'. Ran 129 joints 7", 23#, K-55, ST&C casing 5333' set at 5347'. DV tool at 3544'. Cemented 1st stage with 380 sks Class B with 1% CaCL2, 10#/sk Gilsonite and 1/4#/sk Flocele (486 cu. ft.). Plug down 4:50 pm 10/11/98. Opened DV tool and circ 4 sks to surface. Cemented 2nd stage with 670 sks 65/35 poz with 6% gel, 1% CaCL2, 10#/sk Gilsonite and 1/4# sk Flocele followed by 100 sks Class B with 1% CaCL2, 10#/sk Gilsonite and 1/4# Flocele (1401 cu. ft.). Circ. 53 sks cement to surface. WOC 12 hrs. Tested casing to 1200 psi - OK.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Production Superintendent Date 10/15/98

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC

NOV 03 1998
FARMINGTON DISTRICT OFFICE
BY [Signature]