

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐		98 DEC -8 PM 12:14		5. LEASE DESIGNATION AND SERIAL NO. SF-080657	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other		070 FARMINGTON, NM		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR Taurus Exploration U.S.A., Inc.				7. UNIT AGREEMENT NAME San Juan 32-5 Unit	
3. ADDRESS AND TELEPHONE NO. 2198 Bloomfield Highway; Farmington, NM 87401				8. FARM OR LEASE NAME, WELL NO. San Juan 32-5 Unit 9R	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1300' FNL, 720' FEL Lot 1 At top prod. interval reported below At total depth				9. API WELL NO. 30-039-25999	
14. PERMIT NO.				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T32N, R5W, N.M.P.M.	
15. DATE SPUDDED 9/30/98		16. DATE T.D. REACHED 10/14/98		18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6648 GR	
17. DATE COMPL. (Ready to prod.) 12/7/98		19. ELEV. CASINGHEAD 6648		23. INTERVALS DRILLED BY ROTARY TOOLS X CABLE TOOLS	
20. TOTAL DEPTH, MD & TVD 6410'		21. PLUG, BACK T.D., MD & TVD 6086'		22. IF MULTIPLE COMPL., HOW MANY*	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)* 4672' - 6086' Mesa Verde				25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN Micro Log, Temp. Log, HRI Log, Den.-Neu. Log, GR-CCL-CBL				27. WAS WELL CORED Yes	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)	
9 5/8"		36		240'	
7"		23		5347'	
29. LINER RECORD					
SIZE		TOP (MD)		BOTTOM (MD)	
4 1/2" 10.5#		5166		6403	
30. TUBING RECORD					
SIZE		DEPTH SET (MD)		PACKER SET (MD)	
2 3/8		6074'		5269'	
1 1/2		5098'			
31. PERFORATION RECORD (Interval, size and number) Size 0.34: 5913, 15, 17, 28, 30, 32, 34, 36, 38, 40, 42, 44, 51, 84, 86, 88, 89, 6002, 04, 06, 08, 10, 16, 18, 20, 22, 43, 57, 66, 74, 79, 82, 84, 86 (34 Holes) 1JSPF cont'd next page					
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED			
5913' - 6086'		78,100 Gallons, Slickwater,			
		98,000# 20/40 Sand.			
5416' - 5863'		90,300 Gallons, Slickwater,			
		90,000# 20/40 Sand.			
33.* PRODUCTION					
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) Flowing			WELL STATUS (Producing or shut-in) Shut-In (9 days)
DATE OF TEST 12/7/98		HOURS TESTED 216 HRS	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL - BBL.
FLOW. TUBING PRESS. SI-857		CASING PRESSURE SI-875	CALCULATED 24-HOUR RATE	OIL - BBL.	GAS - MCF.
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To Be Sold					
35. LIST OF ATTACHMENTS None					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					
SIGNED		TITLE Production Superintendent			

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP TRUE VERT. DEPTH
			31. 5416, 52, 80, 94, 5520, 54, 70, 5605, 19, 42, 61, 70 89, 5709, 10, 32, 34, 36, 40, 5808, 10, 26, 28, 30, 32, 40, 42, 44, 46, 48, 54, 56, 59, 61, 63 (35 Holes) 1JSPF	Ojo Alamo	2692	
			4672, 4693, 4704, 10, 18, 60, 68, 75, 85, 95, 4807, 23, 30, 35, 40, 45, 53, 4921, 40, 46, 59, 68, 75, 80 86, 97, 5005, 15, 60, 66, 78, 86, 5105, 15, 23, 24, 5150, 5160 (38 Holes) 1JSPF	Kirtland	2840	
				Fruitland	3225	
				Pictured Cliffs	3430	
				Lewis	3737	
				Huerfano Benton	4480	
				Cliff House	5390	
				Menefee	5763	
				Point Lookout	5921	
			32. 4672' - 5160' - 82,500 Gallons, 60 Q Foam, 150,000# 20/40 Sand.			