

Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
880'FSL, 2210'FWL Sec.33, T-31-N, R-11-W, NMPM,

API # (assigned by OCD)

5. Lease Number
Fee

6. State Oil&Gas Lease
Fee

7. Lease Name/Unit Name
Myra Cummins

8. Well No.
1

9. Pool Name or Wildcat
Basin Dakota

10. Elevation:
County

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

09-18-92 MOL&RU. Blow down. Kill w/55 BW. ND WH. NU BOP. Unable to free packer, locate @ 6615'. PU to 6610', cut tbg free. TOOH w/tbg. SD for weekend.

09-21-92 TIH to 2000'. Pump down tbg, circ 15 bbl oil to flow back tank. Set cmt ret @ 6568'. PT tbg 1500#, ok. Sting into ret. Est inj rate. Cmt plug #1 w/45 sx cmt, 40 sx below ret, 5 sx on top of ret. PU to 6474'. Spot 9 bbl 9# 50 vis mud 6474-5870'. Pull tbg to 5800', circ clean. Perf 2 holes @ 5870'. Set cmt ret @ 5800'.

09-22-92 Pump down tbg, press to 2000#, bled off to 100/10 min. Sting out. Circ hole. Sting into ret. Press to 2000#, bled to 100#/10 min. Pull out of ret. Cmt plug #2 w/20 sx cmt, displace w/18 BW. Sting into ret. Squeeze 12 sx below ret & out perfs @ 5870'. Sting out, dump 8 sx on top of ret. Pull to 5647'. Spot 30 bbl. 9# 50 vis mud up to 3753'. Perf 3 holes @ 3753'. Set cmt ret @ 3708'. Est inj rate. Cmt plug #3 w/67 sx cmt. Displace 61 sx below ret, 6 sx on top of ret. TOOH to 3617'. Spot 20 bbl. 9# 50 vis mud 3617-2307'. TOOH to 2319'. Cmt plug #4 w/12 sx cmt 2319-2161'. TOOH. Perf 2 holes @ 1940'. Set cmt ret @ 1856'. Est inj rat into perfs. Cmt plug #5 w/67 sx cmt, displace 61 sx below ret, 6 sx on top of ret. TOOH to 1762'. Spot 14 bbl. 9# 50 vis mud 1762-883'. TOOH. SDFN.

(cont'd on back)

SIGNATURE

Regulatory Affairs September 24, 1992

(This space for State Use)

Approved by Original Signed by CHARLES GHOLSON

Title

DEPUTY OIL & GAS INSPECTOR, DIST. 43

Date

SEP 28 1992

09-23-92 Perf 2 holes @ 883'. Set cmt ret @ 833'. Est inj rate. Cmt plug #6 w/166 sx cmt, 144 sx below ret, 22 sx on top of ret. Perf 2 holes @ 381'. Est circ down csg & out bradenhead. Cmt plug # 7 w/130 sx cmt, circ 1.5 bbl good cmt out bradnhead. Cut off WH. Install dry hole marker. Released rig. Well plugged & abandoned