


(SUBMIT IN TRIPLICATE)

Indian Agency Ute Mountain Tribal
Allottee 14-20-60-88
Lease No. _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "C"

Farmington, New Mexico February 6, 1959

Well No. 3 is located 1980 ft. from S line and 1980 ft. from E line of sec. 34
SE 1/4 of Section 34 T14N R15W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Verde-Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5424 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ute Mountain Tribal "C" Well No. 3. On January 29, 1959, 5-1/2" casing was set at 4259' with two stagetool at 3830'. Cemented first stage with 75 sacks 6% gel cement with 2 pounds Tuf Plug per sack. Lost returns during last 4 barrels displacement. Opened ports of 2-stage tool and circulated for 4 hours with no cement returns. Cemented second stage with 350 sacks 6% gel cement with 2 pounds Tuf Plug per sack. No returns during last 15 barrels displacement. Top cement by temperature survey 3300'. Drilled out 2-stage tool and cleaned out to bottom. Displaced mud with oil. Released rotary rig on January 30, 1959. Moved in completion unit on February 1, 1959 and tested casing and fracs head with 3000 pounds pressure for thirty minutes, which held with no drop in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487
Farmington, New Mexico

ORIGINAL SIGNED BY
R. M. Bauer, Jr.

By _____
Title Field Engineer

