

(SUBMIT IN TRIPLICATE)

Indian Agency UTE MOUNTAIN



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____
Lease No. 14-20-604-90

JOHN BULETSKY
ACTING DISTRICT ENGINEER

NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

RECEIVED
APR 1 1963
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

MARCH 15, 1963

Well No. 1 is located 1850 ft. from S line and 2110 ft. from E line of sec. 32
N 1/4 Sec. 32 T-31N R-15W N 1/4 M
(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
VERDE GALLUP SAN JUAN NEW MEXICO
(Field) (County or Subdivision) (State or Territory)

~~GROUND LEVEL~~
The elevation of the derrick floor above sea level is 5383 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 1) SET A 100 FT. PLUG AT CASING SHOE
- 2) FIND THE FREE POINT ON CASING AND RECOVER SAME
- 3) SPOT 50 FT. CEMENT INSIDE THE STUB AND 50 FT. OUTSIDE THE STUB
- 4) SPOT 100 FT. CEMENT PLUG FROM 600 FT. TO 700 FT.
- 5) ERECT DRY HOLE MARKER WITH 10 BX CEMENT AT SURFACE



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company A.L. DUFF, JR.

Address 515 SIMMS LLDC.

ALBUQUERQUE, NEW MEXICO

By _____

Title _____

APPROVED

APR 1 1941

APPROVED FOR
REPRODUCTION