For (F	m 9- eb. 19	331 a (51)	
i			

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa	Fe
Lease No	OF 0784	464
Unit H		

ICE OF INTENTION TO CHANGE PLANS SUBSEQUENT REPORT OF INTENTION TO TEST WATER SHUT-OFF SUBSEQUENT REPORT OF	F WATER SHUT-OFF
SUBSEQUENT REPORT OF	F SHOOTING OR ACIDIZING
	F ALTERING CASING
	F RE-DRILLING OR REPAIR
THE OF INTENTION TO RE-DRIZE ON THE	F ABANDONMENT
SICE OF INTENTION TO SHOOT ON ACIDIZE	HISTORY
OTICE OF INTENTION TO FOLE ON ALTER STATES	
OTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE,	OR OTHER DATA)
	, 19
Gov't Payne ell No. #2-35 is located 1850 ft. from Syline and 290	ft. from $\{E\}$ line of sec. $\mathbb{R}^{\frac{n}{2}}$
NE 35 31N 134 1949	eridian)
(1/4 Sec. and Sec. No.) (Twp.)	Waw Marica
Undesignated Dakota San Juan (Field) (County or Subdivision)	(State or Territory)
tate names of and expected depths to objective sands; show sizes, weights, and lengths of p ing points, and all other important proposed we 4-13-60 T. D. 6898*. Ran 5½** 14 & 15.5# J-5 Comented with 185 sacks 66 gel cement	roposed casings; indicate mudding jobs, cemer ork) i5 casing to 6096°. Pressured pipe
tate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we	roposed casings; indicate mudding jobs, cemer ork) i5 casing to 6096°. Pressured pipe
tate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we depth to be a composed with 185 sacks (6) gel cament	roposed casings; indicate mudding jobs, cemer ork) i5 casing to 6096°. Pressured pipe
tate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we 4-13-60 T. D. 6898°. Ran 5½° 14 & 15.5# J-5 Comented with 185 sacks 66 gel coment	roposed casings; indicate mudding jobs, cemer ork) i5 casing to 6096°. Pressured pipe
ate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we 4-13-60 T. D. 6898°. Ran 5½° 14 & 15.5# J-5 Cemented with 185 sacks 66 gel cement to 2500 psi. Pressure held, pipe CK.	roposed casings; indicate mudding jobs, cementally of casing to 6896. Pressured pipe MAY 9 1960 CON. COM.
ate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we 4-13-60 T. D. 6898°. Ran 5½° 14 & 15.5# J-5 Comented with 185 sacks 66 gel coment to 2500 psi. Pressure held, pipe CK.	roposed casings; indicate mudding jobs, cementally of casing to 6896. Pressured pipe MAY 9 1960 CON. COM.
I understand that this plan of work must receive approval in writing by the Geological Company CONTOLIDATED OIL & GAS, INC.	roposed casings; indicate mudding jobs, cementally of casing to 6896. Pressured pipe MAY 9 1960 CON. COM.
tate names of and expected depths to objective sands; show sizes, weights, and lengths of ping points, and all other important proposed we 4-13-60 T. D. 6898°. Ran 5½° 14 & 15.5# J-5 Cemented with 185 sacks 66 gel cement to 2500 psi. Pressure held, pipe CK.	roposed casings; indicate mudding jobs, cementally of casing to 6896. Pressured pipe MAY 9 1960 CON. COM.