NO. OF COPIES RECEIVED	2	5		Form C-103
DISTRIBUTION	<u> </u>	L		Supersedes Old C-102 and C-103
SANTA FE	1.		NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	/	1		Control Description
U.S.C.S.	 	<u> </u>	•	State FederalFee
LAND OFFICE	!	ļ		State FederalFee 5. State Oil & Gas Lease No.
OPERATOR	1/_	İ		5. State Off & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)				
1. OIL GAS WELL WELL		ļ	OTHER- MAY \$ 1 1372	7. Unit Agreement Name
2. Name of Operator			Company OIL CON. OOK	8/ Farm or Lease Name
El Paso Natu	/ Atlantic B			
3. Address of Operator	9. Well No.			
PO Box 990,	Far	min	gton, NM 87401	7
4. Location of Well				10. Field and Pool, or Wildcat
UNIT LETTER A	·	79	O FEET FROM THE North LINE AND 790 FEET FROM	Blanco Mesa Verde
	•			
THEEast	.INE,	SECTI	N 34 TOWNSHIP 31N RANGE 10W NMPM.	
	III		15, Elevation (Show whether DF, RT, GR, etc.)	12. County
	III	III	6298'GL	San Juan
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK	٦		PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	Ť		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	f		CHANGE PLANS CASING TEST AND CEMENT JOBS	
POCE ON ALIZA CASING	_		OTHER	
other Squeeze,	cas	se c	ement, perf & frac	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
In order to increase production it is planned to workover and restimulate this well in the				
following manner:				
Pull tubing, set a drillable bridge plug near the bottom of the 7" casing and pressure test				
to 1000 psi.				
If tubing is stuck, cut off tubing approximately 100' below the 7" casing shoe, set a drillable				
cement retai	ner	nea	r the bottom of the 7" casing, squeeze the open hole	with approximately
150 sks. of cement.				
			casing to 1000 psi.	
Isolate and squeeze cement any leaks. If leaks are squeezed near the base of the Ojo Alamo				
formation, no additional block squeeze of the 7" annulus is planned.				
If there are no leaks near the base of the Ojo Alamo formation, perforate 1 squeeze hole at the				
base of the Ojo Alamo formation and block squeeze the 7" annulus with approximately 125 sks.				
of cement.				
Clean out if hole conditions permit, otherwise sidetrack and redrill to approxima tely 5665'.				
			4 1/2" production casing and sufficient amount of cer	
			ectively perforate and sand-water fracture the Mesa	
/ Casing sin			outroly policiate and band mater illustrate the most	
18. I hereby certify that the	infort \	nation	above is true and complete to the best of my knowledge and belief.	
V. 4/ /)	(34 00 1070
SIGNED 4/0 M	20	2	Petroleum Engineer	May 22, 1972
(a. 1		1,	SUPERVISOR DIST. #3	MAY 2 ± 1972
APPROVED BY TITLE TITLE DATE				
CONDITIONS OF APPROVAL, IF ANY:				