Form 9-331

## UNITED STATES

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424

DEP.	SF 080917				
SUNDRY (Do not use this form for Use "A	NOTICES AND REPORTS ( proposals to drill or to deepen or plug PPLICATION FOR PERMIT—" for such p	ON WELLS back to a differently satisfic proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
OIL GAS WELL OF	PHER	JUN 23 197	7. NIT AGREEMENT NAME		
2. NAME OF OPERATOR El Paso Natural Ga	as Company	OIL CON, CON	Helancie B		
3. ADDRESS OF OPERATOR PO Box 990, Farm	ington, NM 87401	0131. 3	9. WELL NO. 7 (OWWO)		
4. LOCATION OF WELL (Report loc See also space 17 below.) At surface	cation clearly and in accordance with any 790'N, 790'E	State requirements.*	10. FIELD AND POOL, OR WILDCAT  Blanco Mesa Verde  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  Sec. 34, T-31-N, R-10-W NMPM		
14. PERMIT NO.	15. FLEVATIONS (Show whether D	F, ET, GR, etc.) 6298'GL	12. COUNTY OR PARISH 13. STATE San Juan New Mexico		
16. Che	ck Appropriate Box To Indicate I	Nature of Notice, Report, or (			
NOTICE O	F INTENTION TO:	SUBSEQ	SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF  FRACTURE TREATMENT SHOOTING OR ACIDIZING  (Other)  (Note: Report results Completion or Recomp	REPAIRING WELL  ALTERING CASING  ABANDONMENT*  Squeeze  S of multiple completion on Well  detion Report and Log form.)		
on 6-2-72, cut off Squeezed open hole	stuck tubing at 4746', pulled with 150 sacks cement.	ed tubing and set cemen	:		
on 6-3-72, found h at 2628' with 125 s	ole in 7" casing at 2628', sacks cement.	set cement retainer at 2	255U, squeezed leak		

on 6-7-72, sidetrack T.D. 5679'. Ran 177 joints 4 1/2", 10.5#, KE production casing, 5668' set at 5679' with 125 sacks cement. WOC 18 hours. Top of cement at 3170'.

on 6-8-72, PBTD 5666'. Perf 5480-88', 5518-26', 5542-50', 5566-74', 5632-40' with 16 shots per zone. Frac with 42,000# 20/40 sand, 42,084 gallons water, dropped 4 sets of 16 balls, flushed with 3864 gallons water. Dropped bridging ball to baffle at 5434'. Perf 5284-92', 5308-16', 5338-46', 5370-78', 5396-5404' with 16 shots per zone. Frac with 42,000# 20/40 sand, 34,734 gallons treated water, dropped 4 sets of 16 balls, flushed with 3612 gallons water. Set bridge plug at 4900'. Perf 4674-82', 4718-24', 4764-70', 4794-4802', 4812-20', 4852-60' with 16 shots per zone. Frac with 49,000# 20/40 sand, 30,912 gallons treated water. Dropped 5 sets of 16 balls. Balled off on third drop, no flush.

18. I hereby o	ortify that the foregoing is true and correct				
SIGNED _	170 WOOX	TITLE	Petroleum Engineer	date Ju	ne 21. 1972
(This space	ce for Federal or State office use)				77()
APPROVE CONDITION	ED BYONS OF APPROVAL, IF ANY:	TITLE		DATE	JUN 2 1 10/2