

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Window Rock
Allottee Navajo Tribal
Lease No. 11-20-603-731

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sept. 6, 1960

Well No. 16 is located 1930 ft. from N line and 660 ft. from E line of sec. 31
C SE NE 34. 31 31N 16W T4N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Horseshoe-Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~center~~ ground above sea level is 525 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 1130-1162' Schlumberger 1130-1162' Gamma Ray with 61 Jets. Set Baker Model "C" Retractable Bridge Plug at 1165'. Treated above perforations with 2000# 20-80 Sand and 12,000 gals. lease crude. Perforation broke down 3000-6000'. Average treating pressure 105#, average injection rate 35 BPM. Job complete at 8:43 A.M., 8-31-60.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Atlantic Refining Co.
Address P. O. Box 520
Casper, Wyoming

By [Signature]
Title District Superintendent