

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Ute Mountain Tribal
Allottee _____
Lease No. 14-20-60-125

File copy

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

RECEIVED
MAR 4 1960
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "2" Farmington, New Mexico, March 3, 19 60

Well No. 3 is located 440 ft. from N line and 2130 ft. from E line of sec. 35

NE 1/4 of Section 35 T-11-N R-15-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Verde-Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5434 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ute Mountain Tribal "2" Well No. 3 was completed as temporarily abandoned well, Verde-Gallup field on February 16, 1959, as a result of not obtaining any oil or gas in commercial quantities. Well was temporarily abandoned on February 16, 1959 by pulling tubing, removing head, and capping well with 5-1/2" x 2" swage nipple with valve. We now propose to permanently plug and abandon this well as follows:

1. Spot 55 sacks cement plug on bottom (approximately 450 ft. of fill up) and squeeze with minimum pressure to leave perforations covered by cement.
2. Fill hole with fluid.
3. Pump 50 sacks cement down 5-1/2"-8-5/8" annulus to anchor pipe.
4. Removed well head and surface equipment.
5. Spot 5 sacks cement for surface plug (0-40') and erect dry hole marker.
6. Plug and abandonment operations by above procedure to permit possible re-entry for future secondary recovery purposes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pac American Petroleum Corporation

Address P. O. Box 467

Farmington, New Mexico

Attn: L. G. Spoor, Jr.

ORIGINAL SIGNED BY

By R. M. Bauer, Jr.

Title Area Engineer