

(SUBMIT IN TRIPLICATE)


Indian Agency \_\_\_\_\_

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

~~Ute Mountain Tribal~~

Allottee \_\_\_\_\_

Lease No. 14-20-60-123



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	<div style="border: 2px solid black; padding: 5px; text-align: center;"> RECEIVED MAR 4 1960 U. S. GEOLOGICAL SURVEY DURANGO, CO. </div>
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	
NOTICE OF INTENTION TO ABANDON WELL <input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "G" Farmington, New Mexico, March 3, 19 60

Well No. 4 is located 990 ft. from S line and 1850 ft. from W line of sec. 26

SW 1/4 of Section 26 T-11-N R-15-W M.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Verde-Gallup San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5461 ft. (GL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

As a result of not obtaining oil or gas in commercial quantities, Ute Mountain Tribal "G" well No. 4 was temporarily abandoned on October 21, 1959 by pulling tubing and installing valve on well head. We now propose to permanently plug and abandon this well as follows:

1. Spot 15 sacks cement plug on bottom (approximately 120 ft. of fill-up) and squeeze with minimum pressure to leave perforations covered by cement.
2. Fill hole with fluid.
3. Pump 50 sacks cement down 5-1/2"-8-5/8" annulus to anchor pipe.
4. Remove well head and surface equipment.
5. Spot 5 sacks cement for surface plug (0-40') and erect dry hole marker.
6. Plug and abandonment operations by above procedure to permit possible re-entry for future secondary purposes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address P. O. Box 487

Farmington, New Mexico

Attn: L. O. Spear, Jr.

ORIGINAL SIGNED BY MAR 7 1960  
R. M. Bauer, Jr.

By OIL CON. COM.  
DIST. 3

Title Area Engineer