

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Undesignated Formation Dakota County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 9/23/60  
Company Artes Oil & Gas Company Lease Thompson Well No. 6-D  
Unit 0 Sec. 27 Twp. 11N Rge. 12W Purchaser \_\_\_\_\_  
Casing 5 1/2 Wt. 34 I.D. 3.012 Set at 7028 Perf. 7020 To 7096  
Tubing 2 3/8 Wt. 4.70 I.D. 1.995 Set at 6945 Perf. Pin collar To \_\_\_\_\_  
Gas Pay: From 7020 To 7096 L 6945 xG 0.70(Mat) -GL 1862 Bar.Press. 12  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 9/16/60 Packer \_\_\_\_\_ Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through 2 3/8" (Choke) Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.		<u>0.750</u>				<u>1724</u>		<u>1724</u>		<u>7 days</u>
2.						<u>119</u>	<u>60(Mat)</u>	<u>183</u>		<u>3 hrs.</u>
3.										
4.										
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.35</u>		<u>161</u>	<u>1.0000</u>	<u>0.9668</u>	<u>1.004</u>	<u>1939</u>
2.							
3.							
4.							
5.							

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-S</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 1796 P<sub>c</sub><sup>2</sup> 3,225.616

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.	<u>497</u>					<u>190.969</u>	<u>3,095.617</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 2030 MCFPD; n 0.75  
COMPANY Artes Oil & Gas Company  
ADDRESS Box 4 578, Farmington, New Mex.  
AGENT and TITLE ORIGINAL SIGNED BY L. M. STEVENS L. M. Stevens, Dist. Engr.  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressibility factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

STATE OF NEW MEXICO	
OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
NUMBER OF COPIES RECEIVED	3
DISTRICT	
SANTA FE	
FILE	
W.S.S.	
LAND	
TRANS. & G. R.	
REG. & T. FILE	
PENALTY	